

EXHIBIT A

United States Patent [19]

Lynch et al.

[11] Patent Number: **4,729,861**[45] Date of Patent: **Mar. 8, 1988**[54] **METHOD OF MAKING GOLF BALLS**[75] Inventors: **Francis deS. Lynch, Mattapoisett;
John W. Jepson, Marion; Robert A.
Brown, Mattapoisett, all of Mass.**[73] Assignee: **Acushnet Company, New Bedford,
Mass.**[21] Appl. No.: **713,298**[22] Filed: **Mar. 18, 1985**[58] Field of Search 156/146, 245; 273/232;
264/219, 239, 293, 299, 320, 325

[56] References Cited

U.S. PATENT DOCUMENTS


4,090,716	5/1978	Martin et al.	273/232
4,142,727	3/1979	Shaw et al.	273/232
4,256,304	3/1981	Smith et al.	273/232
4,346,898	8/1982	Badke	273/232
4,560,168	12/1985	Aoyama	273/232

Related U.S. Application Data

[60] Division of Ser. No. 213,056, Dec. 4, 1980, which is a continuation of Ser. No. 91,087, Nov. 5, 1979, abandoned, which is a continuation of Ser. No. 920,396, Jun. 29, 1978, abandoned, which is a continuation of Ser. No. 816,882, Jul. 18, 1977, abandoned, which is a continuation of Ser. No. 716,100, Aug. 20, 1976, abandoned, which is a continuation of Ser. No. 363,353, May 24, 1973, abandoned, which is a continuation-in-part of Ser. No. 236,318, Mar. 20, 1972, abandoned.

[51] Int. Cl.⁴ **A63B 37/14**[52] U.S. Cl. **264/219; 156/146;
156/245; 264/239; 273/232***Primary Examiner*—Caleb Weston*Attorney, Agent, or Firm*—Lucas & Just[57] **ABSTRACT**

Dimples are arranged on the surface of a golf ball in a manner which makes the golf ball travel further. At least about 80% of the distances between the closest points of the edges of adjacent dimples are less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples are greater than about 0.001 inches.

24 Claims, 18 Drawing Figures

U.S. Patent

Mar. 8, 1988

Sheet 1 of 6

4,729,861

FIG. 1





FIG. 2



U.S. Patent

Mar. 8, 1988

Sheet 2 of 6

4,729,861




FIG. 3




FIG. 4







FIG. 5

U.S. Patent

Mar. 8, 1988

Sheet 3 of 6

4,729,861



U.S. Patent

Mar. 8, 1988

Sheet 4 of 6

4,729,861




FIG. 9







FIG. 10

U.S. Patent

Mar. 8, 1988

Sheet 5 of 6

4,729,861




U.S. Patent

Mar. 8, 1988

Sheet 6 of 6

4,729,861



4,729,861

1

METHOD OF MAKING GOLF BALLS

The present application is a divisional application of application Ser. No. 213,056 filed Dec. 4, 1980 which in turn was a continuation of application Ser. No. 091,087 filed Nov. 5, 1979 and now abandoned, which in turn was a continuation of application Ser. No. 920,396 filed June 29, 1978 and now abandoned, which in turn was a continuation of application Ser. No. 816,882 filed July 18, 1977 and now abandoned, which in turn was a continuation of application Ser. No. 716,100 filed Aug. 20, 1976 and now abandoned, which in turn was a continuation of application Ser. No. 363,353 filed May 24, 1973 and now abandoned, which in turn was a continuation-in-part of application Ser. No. 236,318 filed Mar. 20, 1972 and now abandoned.

The present invention relates to the spatial relationships of dimples on the surface of golf balls. By having most of the adjacent dimples no more than about 0.065 inches apart, the golf ball will travel further than a standard golf ball which is identical except for the spatial arrangement of the dimples.

For many years golf balls have had dimples on their surfaces in order to increase their aerodynamic properties whereby the ball will travel further than a smooth golf ball. By the term "dimple" it is meant an indentation in the surface of a golf ball. There have been various attempts to improve the distance obtained from a golf ball by varying the configuration of an individual dimple such as by making its diameter larger, its depth shallower, or even changing the dimple from a round to a square configuration. It has now been discovered that increased yardage can be obtained from a golf ball in which the spatial relationships of the dimples are controlled so that at least about 80% of the land distances of adjacent dimples are less than about 0.065 inches and at least about 55% of the land distances of adjacent dimples are greater than about 0.001 inches. By the term "land distance" it is intended to mean the distance between the edges of the two dimples at their closest points. The edge of the dimple is defined as the point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple and will be hereinafter more fully explained. Since only about 55% of the land distances are greater than about 0.001 inches, it will be understood that some of the dimples may overlap. Overlapping dimples may have a negative land distance as land distance is herein defined.

It has further been discovered that when the land area between adjacent dimples is controlled within the limits as set forth in this specification, the relative size and number of the dimples is unimportant. Standard golf balls contain about 336 ± 10 dimples on their surface. It has been found that the number of dimples on the golf ball can be varied substantially and that increased yardage will still be obtained when the limits on land distances as taught in this specification and claims are followed. It has additionally been found that the shape of the dimple is not critical. Although the preferred dimple is round, the dimple may be oval, pentagonal, hexagonal, octagonal or other shapes. In addition, more than one shape of dimple may be used on a single ball, if desired. When the term diameter is used herein, it is defined as the distance from edge to edge when the dimple is circular. When the dimple is non-circular, the term diameter is defined as the diameter of a circle which would have the same area as the area of the

2

non-circular dimple. When the term depth is used herein it is defined as the distance from the continuation of the periphery line to the deepest part of a dimple which is a section of a sphere. When the dimple is not a section of a sphere, the depth in accordance with the present invention is computed by taking a cross section of the dimple at its widest point. The area of the cross section is computed and then a section of a circle of equal area is substituted for the cross section. The depth is the distance from the continuation of the periphery line to the deepest part of the section of the circle. Golf balls according to the present invention have been made with 122 dimples, 182 dimples, 252 dimples, 332 dimples and 392 dimples among others.

The critical values in accordance with the present invention are that at least about 80% of the distances between the closest points of the edges of adjacent dimples must be less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples must be greater than about 0.001 inches.

There is additional advantage in controlling the depth to diameter ratio of the individual dimples. In determining the depth to diameter ratio it is necessary to include the number of dimples to be used on the ball. The basic formula for this determination is as follows:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

S=computed unknown (1.0 or less for present invention)

In accordance with the present invention, the computed unknown, S, will always be 1.0 or less. S can be equal to 0 but it will otherwise always be a positive number.

For a golf ball having from about 182 to about 332 dimples, the values of x, y, a, and b in accordance with the present invention will be:

$$y = 0.323 - 0.086N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

N=the exact number of dimples divided by 100

This is designated as Formula 1.

For a golf ball having from 333 to about 392 dimples the same basic formula is used with the following x, y, a, and b values:

$$y = 0.287 - 0.0383N$$

$$x = 0.0162 - 0.00150N$$

$$a = 4.66 - 0.500N$$

$$b = 5.00 - 1.08N$$

N=the exact number of dimples divided by 100

4,729,861

3

This is designated as Formula 2. Again, when S is equal to or less than 1 the depth to diameter relationship is in accordance with the present invention.

For golf balls having from 182 to 332 dimples, even better results are obtained with the basic formula when:

$$y = 0.323 - 0.0896N + 0.122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 4.54 - 2.78N + 0.674N^2$$

$$b = 3.09 - 1.97N + 0.412N^2$$

N = the exact number of dimples by 100

This is designated as Formula 3. It is to be pointed out that all golf balls included in Formula 3 are also included in Formula 1.

For golf balls having from 333 to 392 dimples, even better results are obtained with the basic formula when:

$$y = 0.240 - 0.0242N$$

$$x = 0.0225 - 0.00340N$$

$$a = 13.6 - 3.28N$$

$$b = 5.25 - 1.25N$$

N = the exact number of dimples divided by 100

This is designated as Formula 4. It is to be pointed out that all golf balls included in Formula 4 are also included in Formula 2.

It will be understood that there is not a sharp break between 332 and 333 dimples and that, in fact, the formulas given hereinbefore overlap in this general area. Different sets of formulas have been given for 182-332 and 333-392 dimpled balls only for the purpose of simplification since a single set of formulas for all balls would be unduly complicated. However, no matter which set of formulas is used, best results are obtained when the golf ball has from about 315 to about 340 dimples and the following values are employed in the basic formula:

$$x = 0.0117$$

$$y = 0.156$$

$$a = 1.1$$

$$b = 0.55$$

This is designated as Formula 5. Golf balls which are within this best results formula will also be included within Formulas 2 and 4 and thus necessarily within Formulas 1 and 3.

The preferred method of applying the formulas is to plot a graph of d vs. D vs. N, holding S at 1. (For Formula 5, since there is no "N" in the formula the graph will simply be a plot of d vs. D holding S at 1). The plotting of this graph is well within the skill of the art. Once the graph has been plotted, selection of one of the variables on the graph will automatically yield the other two variables.

An alternative method of applying the formulas is to first select the number of dimples to be used and then arbitrarily select a diameter and depth. If when these numbers are inserted in the appropriate formula $S = 1$ or less, then the depth and diameter are in accordance with the present invention. For Formula 5, the depths and diameters can be the same whether the number of dimples is about 315 or about 340 or any number therebetween.

The following will serve as illustrative examples of selecting diameter and depth according to the present

4

invention. Of course, the dimples were positioned on the ball in accordance with the present invention.

EXAMPLE 1

In this case it was decided to have 252 dimples which comes within Formula 1. The diameter was selected as 0.175 inches and the depth as 0.0145 inches. These values were substituted into Formula 1 and S computed as about 1.9. Since S is greater than 1.0, the depth to diameter relationship is not in accordance with the present invention.

EXAMPLE 2

Example 1 was repeated holding the dimple number at 252 and the diameter at 0.175 inches. In this case, however, the depth of the dimple were decreased to 0.0135 inches. When these values were substituted into Formula 1, S equalled about 0.7 which is less than 1.0 and thus the depth to diameter relationship was in accordance with the present invention. These distances are shown on FIG. 2 since they are within the present invention.

EXAMPLE 3

Example 2 was repeated using the same values i.e., 252 dimples, diameter of 0.175 inches and depth of 0.0135 inches. In this case, however, the values were substituted into Formula 3 to find out whether or not these values give "better" results. S was computed to be about 2.3 which is greater than 1.0 thereby indicating that these values, while within the present invention, do not give "better" results.

EXAMPLE 4

Example 3 was repeated holding the dimple number at 252 and the diameter at 0.175 inches but in this case the depth of the dimple was decreased to 0.0125 inches. When these values were substituted into Formula 3, S equalled about 0.4 which is less than 1.0 thereby indicating that these values give "better" results.

EXAMPLE 5

In this case it was decided to use 392 dimples, which comes within Formula 2. The diameter was selected as 0.130 inches and the depth as 0.009 inches. When these values were substituted into Formula 2, S was found to be about 3.0. Since S is greater than 1, the depth and diameter are not in the proper ratio in accordance with the present invention.

EXAMPLE 6

Example 5 was repeated holding the number of dimples at 392 and the depth at 0.009 inches. However, the diameter was increased to 0.140 inches. In this case S is 0.6 which is less than 1.0 and thus the depth to diameter relationship is within the limits of the present invention.

EXAMPLE 7

When Example 6 was repeated using the same values, i.e., 392 dimples, depth of 0.009 inches and diameter of 0.140 inches, but using Formula 4, S was computed to be 2.3. Since Formula 4 is the formula to be used to obtain "better" results and since the values of this example give a value greater than 1.0 in Formula 4, it is seen that these values, while within the present invention, do not give "better" results.

5

EXAMPLE 8

Example 7 was repeated holding the dimple number at 392 and the depth at 0.009 inches but in this case the diameter was increased to 0.145 inches. When these values were substituted in Formula 4, S was found to be 0.1. Since S is less than 1.0, these values give "better" results.

EXAMPLE 9

In this case it was decided to have 315 dimples which comes within the best results formula i.e., Formula 5. The diameter was selected as 0.150 inches and the depth as 0.0125 inches. These values were substituted into Formula 5 and S computed as about 0.8. Since S was less than 1.0, the depth to diameter relationship is within the "best results" of the present invention.

EXAMPLE 10

Example 9 was repeated using the same depth and diameter i.e., 0.150 inches and 0.0125 inches but in this case the golf ball had 340 dimples. Again, the S value equalled 0.8 and thus the ball was within the "best results" region of the present invention.

These and other aspects of the present invention may be more fully understood with reference to the following drawings in which:

FIG. 1 is the top half of a golf ball with dimples arranged as in today's standard golf ball;

FIG. 2 is the top half of a golf ball showing dimples in accordance with the present invention;

FIGS. 3-5 are cross sections of dimples showing the method of determining the edge of the dimple;

FIGS. 6-9 show a series of dimples and illustrate what is an "adjacent" dimple;

FIGS. 10-13 show one suitable method of arranging the dimples on the surface of the golf ball;

FIG. 14 shows the method of measuring the depth and diameter of a spherically shaped dimple;

FIGS. 15 and 16 show the method of computing the diameter of an irregularly shaped dimple; and

FIGS. 17 and 18 show the method of computing the depth of an irregularly shaped dimple.

Referring now to FIG. 1, there is seen a golf ball partially in section with dimples arranged in the manner customarily employed today. Virtually, all golf balls on the market today have dimples arranged in accordance with this pattern. For each hemisphere of the golf ball 10, the dimples 12 are arranged in two large rectangles 14 and 16, two small rectangles 18 and 20, and four triangles 22, 24, 26, and 28. Because of molding techniques, the opposite side of the golf ball virtually always has the same dimple pattern. It has been found that more than 33% of the land areas of adjacent dimples are more than 0.065 inches apart in this golf ball, even if the dimples are as large as 0.155 inches.

In FIG. 2 there is shown a golf ball made in accordance with the present invention. As indicated on the drawing, at least about 80% of the land areas of adjacent dimples are no greater than about 0.065 inches and no more than about 55% of the land areas of adjacent dimples are less than about 0.001 inches. As can be seen with reference to dimples 30 and 32, the distance between the closest points of these two dimples may be more than 0.065 inches. It is only necessary that the distance between adjacent dimples be less than 0.065 inches for at least about 80% of such distances. Similarly, as can be seen with reference to dimples 36 and 38,

4,729,861

6

there is a negative distance between the edges of the dimple since the edges overlap. In accordance with the present invention it is only necessary that at least about 55% of the distances between dimples at their closest points be greater than 0.001 inches. However, where the dimples overlap, the negative distance should in most cases be no greater than about 0.02 inches. The size of the dimples is relatively unimportant and can be varied within the diameters and depths as given hereinbefore. Different size dimples may be used on the same golf ball, if desired, provided that the critical distances between the edges of adjacent dimples at their closest points is maintained within the values as set forth herein.

Referring to FIGS. 3-5, there is seen the method of determining the point which comprises the edge of the dimple. The edge of the dimple is defined as that point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple, said tangent being at a point about 0.003 inches from the periphery of the ball or its continuation.

In FIG. 3 is seen in cross section a golf ball having periphery 40 and continuation thereof 41 and dimple 12. The periphery and its continuation are a substantially smooth section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects the dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery 40 at points C and D respectively. Points C and D are the edges of the dimple.

In FIG. 4 is seen a golf ball with dimple 12 which has a rounded top 44. The dimple, in three dimensions, is a section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery continuation 41 at points E and F respectively. Points E and F are the edges of the dimple.

Turning now to FIG. 5 there is shown a golf ball in cross section having dimples 12 and 12' partially shown with rounded tops 44 and 44'. Arc 42 is about 0.003 inches below curve 41-40-41 and intersects dimples 12 and 12' at points B and G respectively. Tangent 43' and 43'' are tangent to the dimples 12 and 12' at points B and G respectively. Tangents 43' and 43'' intersect periphery continuation 41 at points F and H respectively. Points F and H are the edges of dimples 12 and 12' respectively. The "land distance" between dimples 12 and 12' is measured along curve 41-40-41 from point F to point H.

Referring to FIGS. 6-9 there is seen the method of determining what is an "adjacent" dimple. An adjacent dimple is defined as one in which a triangle constructed of lines passing through the center points of 3 dimples has no included angle less than about 30°, and has no part of another dimple included therein.

Turning now to FIG. 6 there are shown 4 dimples, 45, 46, 48 and 50, having centers 52, 54, 56, and 58 respectively. If the center point of dimples 46, 48 and 50 are joined by lines, a triangle is formed having sides 60, 62, and 64 as shown. As can be seen, each of the included angles in this triangle is greater than about 30° and no part of another dimple is included within the triangle. Therefore, dimple 46 is adjacent to dimple 48, dimple 46 is adjacent to dimple 50, and dimple 48 is adjacent to dimple 50. Since in accordance with the present invention all dimples are circular or are converted to the circular, the closest points between the

4,729,861

7

two dimples on the edges of the dimple will fall on the line which passes through the center of the two adjacent dimples. The closest points at the edges between dimples 46 and 48 are edge points 66 and 68, and therefore, the critical land distance as described hereinbefore is measured between points 66 and 68 for these adjacent dimples.

In FIG. 7 is shown a set of dimples 70, 72, 74, 76, 78, and 80, having centers 82, 84, 86, 88, 90, and 92, respectively. As shown with reference to FIG. 6, dimples 76 and 78 are "adjacent." If a triangle is formed by drawing lines through the center points of dimples 72, 78, and 76, it is seen that dimples 72 and 78 are not adjacent since the included angles formed by lines 94, 96, and by lines 94, 98 are less than 30°.

Referring to FIG. 8, there is again shown dimples 70, 72, 74, 76, 78, and 80, as well as dimples 100, 102 and 104. Lines 106, 108, and 110 form a triangle, passing through the centers of dimples 72, 78 and 104. Each of the included angles of this triangle is greater than 30°. However, dimple 72 is not adjacent to dimple 78 since at least a part of another dimple is included within the triangle. In this case, the entire dimple 76 is included within the triangle and half of the dimple 80 is included within the triangle.

In FIG. 9 is shown a series of dimples 112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 136, 138, 140, 142, 144, 146, and 148. Referring to dimple 130, dimples 120, 122, 128, 132, 138, and 140 are adjacent thereto since a triangle can be formed with lines passing through the center points of each of these dimples without including at least a portion of another dimple and each included angle of the said triangles will be greater than about 30°. None of the dimples 112, 114, 116, 118, 124, 126, 134, 136, 142, 144, 146, or 148 are adjacent to dimple 130 since no triangle can be drawn through the center point of three dimples including one of these dimples and dimple 130 which will not include at least a section of another dimple and which will have no angle of the triangle less than about 30°.

With further reference to FIG. 9, it will be understood that for dimple 122, adjacent dimples are 114, 116, 120, 124, 130 and 132. With reference to the dimple 140, the adjacent dimples are 130, 132, 138, 142, 146, and 148 and so forth with respect to each of the dimples. For determining the critical values of having at least about 80% of the dimples being no further apart than about 0.065 inches and at least about 55% of the dimples being no closer than about 0.001 inches, the distance between each dimple and each of its adjacent dimples is measured. However, duplicate measurements are not included. Thus, with respect to dimple 130, the distance between it and dimples 120, 122, 128, 132, 138, and 140, are included, but thereafter with respect to the dimple 122, the distance between it and dimple 130 would not be included since this has already been included with respect to dimple 130.

Maximum benefit is obtained when 100% of adjacent dimples have a distance between them at their closest points of less than about 0.065 inches and when 100% of the minimum distances between the closest points of adjacent dimples are greater than about 0.001 inches.

The mechanics of positioning the dimples on the golf ball is not our invention. One suitable method is to first determine the diameter of the dimple to be used. The diameter of the dimple is preferably within the range of about 0.125 inches to about 0.245 inches. The golf ball surface is then broken down into an icosahedron which,

8

in effect, triangulates the surface of the golf ball as shown partially in FIG. 10. Each of the "triangles" of the icosahedron is equilateral as shown in FIG. 11. Vertex dimples 150, 152, and 154 are situated on each of the vertices of the triangle as shown with the center of the dimple being at the vertex of each angle. Additional dimples are then situated on the sides of the "triangle." The positioning of their centers is determined by the diameter of the dimple and the "land distance" between adjacent dimples which is held within the limits as previously given. The additional dimples on the sides of the "triangle" are shown in FIG. 12. Great circles are then made between dimples which are about equidistance from the vertex dimples connecting all of the center points of the dimples on the sides of the "triangle." Additional dimples are placed where these great circles intersect. As shown in FIG. 13, these great circles intersect at points 156, 158, and 160. These points are the center points for additional dimples. This procedure is then followed with respect to each of the other "triangles" of the icosahedron. Naturally, a dimple at the vertex of three contiguous "triangles" will be a vertex dimple for each of the three triangles. It will be understood that the number of dimples on the sides of the "triangle" will vary inversely with the diameter of the dimple. According to the number of dimples on the sides of the "triangle," the number of great circles will also vary and therefore the number of dimples within the "triangle" will also vary since an additional dimple is placed wherever the great circles intersect.

The above method is only illustrative and need not be adhered too rigidly and the dimples need not be evenly spaced so long as the spacing of the dimples is within the critical limitations as hereinbefore given. Golf balls are usually made with two mold "halves" and it is convenient to adjust the dimples in the vicinity of the mold line so that no dimples fall on the partition line of the molds. In this manner, there is less difficulty in removing any "flash" from a dimple.

In FIG. 14 is shown the method of measuring the depth and diameter of a spherically shaped dimple. The dimple in this case is shown in cross section and is the same dimple as shown in FIG. 4. The diameter is measured from the edges of the dimples, points E and F, along line 162 which is a straight line. Point J is the deepest part of the dimple 12. The depth is measured from point K on the continuation of the periphery 41 to point J and is indicated by line 164. Line 164 is perpendicular to line 162.

In FIGS. 15 and 16 is shown the method of computing the diameter of an irregularly shaped dimple. FIG. 15 shows the top of a hexagonally shaped dimple as one looks directly at it and all six sides 164 are shown at the edges of the dimple. The area of the hexagonally shaped dimple is approximately 0.01765 square inches. FIG. 16 is a circle which has an equivalent area to the hexagonal area of FIG. 15 i.e., the area of the circle of FIG. 16 is 0.01765 square inches. The diameter of FIG. 16 is shown as 166 and this diameter is approximately 0.150 inches. Thus, in accordance with the present invention, the diameter of the hexagonally shaped dimple of FIG. 15 is 0.150 inches. It is important to note that the diameter of an irregularly shaped dimple is not measured directly on the irregularly shaped dimple but is always a diameter of a circle which has an area equivalent to that of the irregularly shaped dimple.

In like manner, the depth of an irregularly shaped dimple is computed on the basis of a spherically shaped

9

4,729,861

dimple. In FIG. 17 is shown a cross section of an irregularly shaped dimple which in this case is the same dimple as is shown in FIG. 15. For purposes of determining the depth of the dimple, the cross section is always taken across the widest part of the dimple which passes through the deepest part of the dimple. The edge of the dimple is shown at points L and M and was determined in accordance with the present invention as set out in FIGS. 3 and 4. The periphery is shown at 41 and the deepest point of the dimple is shown at point N. The area of the cross section of the dimple up to the continuation of the periphery (as shown, enclosed by lines M,N, N,L, and L,M along line 41) is computed and found to be 0.00113 square inches. The equivalent area of a section of a circle is then substituted for the dimple as shown in FIG. 18. Points O and P are the edges of the diameter of an equivalent dimple as determined in accordance with FIGS. 15 and 16 and line 168 is a straight line between lines O and P and corresponds to the diameter line 166 of FIG. 16. Point R is the deepest part of the dimple and line 170 is perpendicular to line 168. Line 170 intersects the continuation of the periphery 41 at point S and the depth as measured from point S to point R is 0.0113 inches. It is important to note that in accordance with the present invention the depth of the dimple is measured from a cross section of a circle having an equivalent area to that of a cross section of the irregularly shaped dimple rather than being measured on the actual dimple.

In all cases, measurements made in accordance with the present invention are made on a finished golf ball, since it is the final form of the golf ball which affects aerodynamic properties as opposed to some intermediate construction of the golf ball. In most cases, a finished golf ball will have one or more layers of paint affixed to the surface thereof and in these cases the measurements are made after the final coat of paint or other surface finish has been applied. With some of the new solid balls, however, a finished ball will not have any surface layer such as paint since it is not necessary. It will be understood that in these cases a finished ball means a ball that is unpainted. It will therefore be understood that the term "finished ball" can cover either a painted or an unpainted ball but in either case means the completed ball in the form in which it is intended to be sold to the consumer.

It will be understood that the claims are intended to cover all changes and modifications of the preferred embodiments of the invention, herein chosen for the purpose of illustration, which do not constitute departures from the spirit and scope of the invention.

What is claimed is:

1. A method of manufacturing a golf ball having dimples in the outer periphery thereof comprising the steps of:

- (A) selecting a golf ball structure onto the surface of which dimples can be molded;
- (B) determining the dimple number, dimple diameter and dimple depth by:
 - (a) selecting the number of dimples to be used, the said number of dimples being between 182 and 392;
 - (b) selecting a dimple diameter and dimple depth that satisfy the following relationship:

10

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

in which:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

and wherein:

a value N is obtained by dividing the exact number of dimples by 100, and x, y, a and b are defined by the following relations as functions of N: when the number of dimples is between 182 and 332:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

and when the number of dimples is between 333 and 392:

$$y = 0.287 - 0.0383N$$

$$x = 0.0162 - 0.00150N$$

$$a = 4.66 - 0.500N$$

$$b = 5.00 - 1.08N$$

(C) making golf ball molds by positioning the selected dimples on the golf ball mold so that the surface of the golf ball made therefrom will have at least 80% of the distances between the closest points of the edges of adjacent dimples less than about 0.065 inches, and at least 55% of the distances between the closest points of the edges of adjacent dimples greater than 0.001 inches the edge of the dimples being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimples at a point 0.003 inches below the periphery of the golf ball or its continuation;

(D) forming the dimples on the surface of the golf ball by molding a golf ball in the mold;

(E) removing the formed golf ball from the mold; and

(F) finishing the golf ball.

2. The method of claim 1 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.065 inches.

3. The method of claim 1 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distance between the edges of adjacent dimples is greater than 0.001 inches.

4. The method of claim 1 wherein the dimples are circular.

5. The method of claim 1 wherein the selected number of dimples is from 182 to 332 and x, y, a and b are defined by the following relations as functions N:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

4,729,861

11

$$x=0.0186-0.00406N+0.000550N^2$$

$$a=4.54-2.78N+0.674N^2$$

$$b=3.09-1.97N+0.412N^2.$$

6. The method of claim 5 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.065 inches.

7. The method of claim 6 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is greater than 0.001 inches.

8. The method of claim 6 wherein the dimples are circular.

9. The method of claim 1 wherein the selected number of dimples is from 333 to 392 and x, y, a and b are defined by the following relations as functions of N:

$$y=0.287-0.0383N$$

$$x=0.0162-0.00150N$$

$$a=4.66-0.500N$$

$$b=5.00-1.08N.$$

10. The method of claim 9 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.0065 inches.

11. The method of claim 9 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of the adjacent dimples is greater than 0.001 inches.

12. The method of claim 9 wherein the dimples are circular.

13. The method of claim 1 wherein the selected number of dimples is from 182 to 332 and x, y, a and b are defined by the following relations as functions of N:

$$y=0.323-0.0896N+0.0122N^2$$

$$x=0.0186-0.00406N+0.000550N^2$$

$$a=6.30-3.30N+0.693N^2$$

$$b=3.09-1.97N+0.412N^2.$$

12

14. The method of claim 13 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.065 inches.

15. The method of claim 13 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is greater than 0.001 inches.

16. The method of claim 15 wherein the dimples are circular.

17. The method of claim 1 wherein the selected number of dimples is from 333 to 392 and x, y, a and b are defined by the following relations as functions of N:

$$y=0.240-0.0242N$$

$$x=0.0225-0.00340N$$

$$a=13.6-3.28N$$

$$b=5.25-1.25N.$$

18. The method of claim 17 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.065 inches.

19. The method of claim 17 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is greater than 0.001 inches.

20. The method of claim 17 wherein the dimples are circular.

21. The method of claim 17 wherein the selected number of dimples is from 315 to 340 and x, y, a and b are as follows:

$$x=0.0117$$

$$y=0.156$$

$$a=1.1$$

$$b=0.55.$$

22. The method of claim 21 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is less than 0.065 inches.

23. The method of claim 21 wherein the positioning of the selected dimples in the surface of the golf ball is such that 100% of the closest distances between the edges of adjacent dimples is greater than 0.001 inches.

24. The method of claim 21 wherein the dimples are circular.

* * * * *

50

55

60

65

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,729,861

Page 1 of 2

DATED : March 8, 1988

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent are hereby corrected as shown below:

Column 1, line 41, delete "the" (second instance).

Column 2, line 48, change "0.086N" to --0.0896N--.

Column 3, line 14, after "dimples" insert --divided--.

Column 3, line 31, change "44" to --4--.

Column 5, line 6, change "in" to --into--.

Column 6, line 47, change "12" " to --12'--.

Column 10, line 67, after "functions" insert --of--.

Column 11, line 12, change the dependency from "claim 6" to --claim 5--.

Column 11, line 16, change the dependency from "claim 6" to --claim 5--.

Column 11, line 32, change "0.0065" to --0.065--.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,729,861

Page 2 of 2

DATED : March 8, 1988

INVENTOR(S) : Francis deS. Lynch et al

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12, line 9, change the dependency from "claim 15" to --claim 13--.

Signed and Sealed this
Eighteenth Day of October, 1988

Attest:

DONALD J. QUIGG

Attesting Officer

Commissioner of Patents and Trademarks

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,729,861

DATED : March 8, 1988

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12, line 32, change the dependency from "claim 17"
to read -- claim 1 --.

Signed and Sealed this
Thirty-first Day of January, 1989

Attest:

DONALD J. QUIGG

Attesting Officer

Commissioner of Patents and Trademarks

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,729,861

Page 1 of 2

DATED : March 8, 1988

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4, line 17, after "dimple" change "were" to
--was--;

Column 5, line 17, change "rest" to --best--;

Column 6, line 43, change "Tangent" to --Tangents--;

Column 7, line 52, change "distance" to --distances--;

Column 8, line 13, change "equidistance" to
--equidistant--;

Column 10, line 61, change "distance" to --distances--;

Column 11, line 36, delete "the"; and

Column 12, line 43, after "0.065" delete "dimples"
and substitute therefor --inches--.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,729,861

Page 2 of 2

DATED : March 8, 1988

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 11, line 50, change " $b=3.09-1.97N+0.412N^2$ "
to $--b=3.11-1.03N+0.155N^2--$.

Signed and Sealed this
Twenty-seventh Day of November, 1990

Attest:

HARRY F. MANBECK, JR.

Attesting Officer

Commissioner of Patents and Trademarks

EXHIBIT B

United States Patent [19]

Lynch et al.

[11] Patent Number: **4,936,587**[45] Date of Patent: **Jun. 26, 1990**[54] **GOLF BALL**[75] Inventors: **Francis deS. Lynch, Mattapoissett; John W. Jepson, Marion; Robert A. Brown, Mattapoissett, all of Mass.**[73] Assignee: **Acushnet Company, New Bedford, Mass.**[21] Appl. No.: **213,056**[22] Filed: **Dec. 4, 1980****Related U.S. Application Data**

[63] Continuation of Ser. No. 91,087, Nov. 5, 1979, abandoned, which is a continuation of Ser. No. 920,396, Jun. 29, 1978, abandoned, which is a continuation of Ser. No. 816,882, Jul. 18, 1977, abandoned, which is a continuation of Ser. No. 716,100, Aug. 20, 1976, abandoned, which is a continuation of Ser. No. 363,353, May 24, 1973, abandoned, which is a continuation-in-part of Ser. No. 236,318, Mar. 20, 1972, abandoned.

[51] Int. Cl.⁵ **A63B 37/14**[52] U.S. Cl. **273/232; 273/218**[58] Field of Search **273/232**[56] **References Cited****U.S. PATENT DOCUMENTS**

D. 27,441	7/1897	Dunn	D21/205
D. 29,949	1/1899	Barnes	D21/205
D. 30,378	3/1899	Foulis	D21/205
D. 34,557	5/1901	Cooper	D21/205
D. 41,327	4/1911	Pearce	D21/205
D. 41,698	8/1911	Royce	D21/205

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

201159	3/1955	Australia	273/232
1005479	2/1977	Canada	273/232
12884	11/1914	United Kingdom	273/232
377354	7/1932	United Kingdom	273/232
757183	9/1956	United Kingdom	273/232
106134	12/1961	United Kingdom	273/232

OTHER PUBLICATIONS

"Voit 1967 Retail Athletic Catalog No. 367", 1967, page unknown; description relates to The Icosahedron.

"The Curious History of the Golf Ball, Mankind's Most Fascinating Sphere", by John Stuart Martin, Horizon Press, N.Y. 1968, pp. 127 to 130.

USGA, "The Rules of Golf," 1970, pp. 12-13.

"Gold-Exercise of One's Brains", p. 208 (Japan).

"A Guide to Golf Ball Engineering", pp. 772-773 (Japan).

"An Evening Newspaper of the Mainichi" (Japan).

"Iwanami's Dictionary of Mathematics", Feb. 20, 1971, pp. 581-582.

"Manual of Mechanical Engineering", Sep. 15, 1970, pp. 2-18.

"Encyclopedia of Science", Oct. 20, 1971, p. 168.

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Lucas & Just

[57] **ABSTRACT**

Dimples on a golf ball are interrelated by dimple number, dimple diameter and dimple depth and are arranged on the surface of the golf ball in a manner which enables the golf ball to travel further. At least about 80% of the distances between the closest points of the edges of adjacent dimples are less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples are greater than about 0.001 inches.

Dimple number, dimple diameter and dimple depth are also interrelated in a specific manner according to the formula:

$$S = \left[\frac{831.5(d - x) - 55.56(D - y)}{a} \right]^2 + \left[\frac{83.15(D - y) + 555.6(d - x)}{b} \right]^2$$


wherein:

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

S=computed unknown (1.0 or less for present invention)

x, y, a and b are dependent on the number of dimples.

37 Claims, 12 Drawing Sheets**315 DIMPLES (FORMULA 1)**

4,936,587

Page 2

U.S. PATENT DOCUMENTS

D. 41,817	10/1911	Pearce	D21/205
D. 42,164	2/1912	Breakspear	D21/205
D. 43,673	3/1913	Johnston	D21/205
D. 44,109	5/1913	Penney	D21/205
D. 44,175	6/1913	Martin et al.	D21/205
D. 44,176	6/1913	Martin et al.	D21/205
D. 44,177	6/1913	Martin et al.	D21/205
D. 44,227	6/1913	Wood	D21/205
D. 44,408	7/1913	Martin et al.	D21/205
D. 46,778	12/1914	Pearce	D21/205
D. 46,783	12/1914	Worthington	D21/205
D. 47,159	3/1915	Kempshall	D21/205
D. 49,905	11/1916	Martin	D21/204
D. 50,512	3/1917	Johnston	D21/205
D. 50,553	4/1917	Cochrane	D21/204
D. 50,883	6/1917	Cochran	D21/204
D. 51,722	2/1918	Eddy	D21/204
D. 52,500	9/1918	Vaice	D21/205
D. 52,706	11/1918	Robertson	D21/205
D. 52,712	11/1918	Turner	D21/205
D. 55,330	5/1920	Robertson	D21/204
D. 59,366	10/1921	Martin	D21/204
D. 60,979	5/1922	Cigol	D21/204
D. 72,692	7/1927	Beldam	D21/204
D. 72,693	7/1927	Beldam	D21/204
D. 73,046	7/1927	Penfold	D21/204
D. 74,213	1/1928	Cigol	D21/204
D. 75,198	5/1928	Young	D21/205
D. 75,422	6/1928	Gioggia	D21/205
D. 78,311	4/1929	Perry	D21/205
D. 79,223	8/1929	Binnie	D21/205
D. 79,224	8/1929	Binnie	D21/205
D. 79,458	9/1929	Des Rosiers	D21/205
D. 80,740	3/1930	Perry	D21/205
D. 91,919	4/1934	Burbank	D21/205
D. 94,403	1/1935	Burbank	D21/205
D. 100,206	6/1936	Davis	D21/205
D. 102,940	1/1937	Cavignac	D21/205
D. 107,066	11/1937	Cavignac	D21/205
D. 108,065	1/1938	Cavignac	D21/205
D. 176,470	12/1955	Martin	D21/205
D. 228,394	9/1973	Martin	273/232
697,417	4/1902	Kempshall	273/218
705,766	7/1902	Kempshall	273/220
710,753	10/1902	Cavanagh	273/230
716,945	12/1902	Selzer	273/230
878,254	2/1908	Taylor	273/232
922,773	5/1909	Kempshall	273/232
1,182,604	5/1916	Wadsworth	273/232
1,182,605	5/1916	Wadsworth	273/214
1,265,036	5/1918	Bendelow	273/232
1,286,834	12/1918	Taylor	273/232
1,418,220	5/1922	White	273/232
1,517,514	12/1924	Hunt	273/232
1,656,408	1/1928	Young	273/232
1,666,699	12/1927	Hagen	273/232
1,681,167	8/1928	Beldam	273/232
1,716,435	6/1929	Fotheringham	273/232
1,855,448	4/1932	Hazeltine	273/232
1,862,708	6/1932	Rosenberg	273/213
2,002,726	5/1935	Young	273/232
2,106,704	2/1938	Davis	273/232
2,135,210	11/1938	Farrar	273/232
2,728,576	12/1955	Martin et al.	273/232
4,090,716	5/1978	Martin et al.	273/232

U.S. Patent

Jun. 26, 1990

Sheet 1 of 13

4,936,587

FIG. 1





FIG. 2






FIG. 3




FIG. 4







FIG. 5

U.S. Patent

Jun. 26, 1990

Sheet 3 of 13

4,936,587



U.S. Patent

Jun. 26, 1990

Sheet 4 of 13

4,936,587




FIG. 9







FIG. 10

U.S. Patent

Jun. 26, 1990

Sheet 5 of 13

4,936,587








U.S. Patent

Jun. 26, 1990

Sheet 6 of 13

4,936,587



U.S. Patent


Jun. 26, 1990

Sheet 7 of 13

4,936,587

FIG. 19.

182 DIMPLES (FORMULA 1)




U.S. Patent Jun. 26, 1990

Sheet 8 of 13

4,936,587

FIG. 20.

252 DIMPLES (FORMULA 1)



U.S. Patent


Jun. 26, 1990

Sheet 9 of 13

4,936,587

FIG. 21.

315 DIMPLES (FORMULA 1)



U.S. Patent


Jun. 26, 1990

Sheet 10 of 13

4,936,587

FIG. 22.

33Z DIMPLES (FORMULA 1)



U.S. Patent


Jun. 26, 1990

Sheet 11 of 13

4,936,587

FIG. 23.

340 DIMPLES (FORMULA 2)



U.S. Patent


Jun. 26, 1990

Sheet 12 of 13

4,936,587

FIG. 24.

392 DIMPLES (FORMULA 2)



U.S. Patent


Jun. 26, 1990

Sheet 13 of 13

4,936,587

FIG. 25.

362 DIMPLES (FORMULA 2)



4,936,587

1

GOLF BALL

The present application is a continuation of application Ser. No. 091,087 filed Nov. 5, 1979 which in turn was a continuation of application Ser. No. 920,396 filed June 29, 1978 which in turn was a continuation of application Ser. No. 816,882 filed July 18, 1977 which in turn was a continuation of application Ser. No. 716,100 filed Aug. 20, 1976 which in turn was a continuation of application Ser. No. 363,353 filed May 24, 1973 which in turn was a continuation-in-part of application Ser. No. 236,318 filed Mar. 20, 1972, all said applications now being abandoned.

The present invention relates to the spatial relationship of dimples on the surface of golf balls. By having most of the adjacent dimples no more than about 0.065 inches apart, the golf ball will travel further than a standard golf ball which is identical except for the spatial arrangement of the dimples.

For many years golf balls have had dimples on their surfaces in order to increase their aerodynamic properties whereby the ball will travel further than a smooth golf ball. By the term "dimple" it is meant an indentation in the surface of a golf ball. There have been various attempts to improve the distance obtained from a golf ball by varying the configuration of an individual dimple such as by making its diameter larger, its depth shallower, or even changing the dimple from a round to a square configuration. It has now been discovered that increased yardage can be obtained from a golf ball in which the spatial relationships of the dimples are controlled so that at least about 80% of the land distances of adjacent dimples are less than about 0.065 inches and at least about 55% of the land distances of adjacent dimples are greater than about 0.001 inches. By the term "land distance" it is intended to mean the distance between the edges of two dimples at their closest points. The edge of the dimples is defined as the point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple and will be hereinafter more fully explained. Since only about 55% of the land distances are greater than about 0.001 inches, it will be understood that some of the dimples may overlap. Overlapping dimples may have a negative land distance as land distance is herein defined.

It has further been discovered that when the land area between adjacent dimples is controlled within the limits as set forth in this specification, the relative size and number of the dimples is unimportant. Standard golf balls contain about 336 ± 10 dimples on their surface. It has been found that the number of dimples on the golf ball can be varied substantially and that increased yardage will still be obtained when the limits on land distances as taught in this specification and claims are followed. It has additionally been found that the shape of the dimple is not critical. Although the preferred dimple is round, the dimple may be oval, pentagonal, hexagonal, octagonal or other shapes. In addition, more than one shape of dimple may be used on a single ball, if desired. When the term diameter is used herein, it is defined as the distance from edge to edge when the dimple is circular. When the dimple is non-circular, the term diameter is defined as the diameter of a circle which would have the same area as the area of the non-circular dimple. When the term depth is used herein it is defined as the distance from the continuation of the periphery line to the deepest part of a dimple

2

which is a section of a sphere. When the dimple is not a section of a sphere, the depth in accordance with the present invention is computed by taking a cross section of the dimple at its widest point. The area of the cross section is computed and then a section of a circle of equal area is substituted for the cross section. The depth is the distance from the continuation of the periphery line to the deepest part of the section of the circle. Golf balls according to the present invention have been made with 122 dimples, 182 dimples, 252 dimples, 332 dimples and 392 dimples among others.

The critical values in accordance with the present invention are that at least about 80% of the distances between the closest points of the edges of adjacent dimples must be less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples must be greater than about 0.001 inches.

There is additional advantage in controlling the depth to diameter ratio of the individual dimples. In determining the depth to diameter ratio it is necessary to include the number of dimples to be used on the ball. The basic formula for this determination is as follows:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

S=computed unknown (1.0 or less for present invention)

In accordance with the present invention, the computed unknown, S, will always be 1.0 or less. S can be equal to 0 but it will otherwise always be a positive number.

For a golf ball having from about 182 to about 332 dimples, the values of x, y, a, and b in accordance with the present invention will be:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

N=the exact number of dimples divided by 100

This is designated as Formula 1.

For a golf ball having from 333 to about 392 dimples the same basic formula is used with the following x, y, a, and b values:

$$y = 0.287 - 0.0383N$$

$$x = 0.0162 - 0.00150N$$

$$a = 4.66 - 0.500N$$

$$b = 5.00 - 1.08N$$

N=the exact number of dimples divided by 100

This is designated as Formula 2. Again, when S is equal to or less than 1 the depth to diameter relationship is in accordance with the present invention.

For golf balls having from 182 to 332 dimples, even better results are obtained with the basic formula when:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 4.54 - 2.78N + 0.674N^2$$

$$b = 3.09 - 1.97N + 0.412N^2$$

N=the exact number of dimples divided by 100

This is designated as formula 3. It is to be pointed out that all golf balls included in Formula 3 are also included in Formula 1.

4,936,587

3

For golf balls having from 333 to 392 dimples, even better results are obtained with the basic formula when:

$$\begin{aligned}y &= 0.240 - 0.0242N \\x &= 0.0225 - 0.00340N \\a &= 13.6 - 3.28N \\b &= 5.25 - 1.25N\end{aligned}$$

N = the exact number of dimples divided by 100

This is designated as Formula 4. It is to be pointed out that all golf balls included in Formula 4 are also included in Formula 2.

It will be understood that there is not a sharp break between 332 and 333 dimples and that, in fact, the formulas given hereinbefore overlap in this general area. Different sets of formulas have been given for 182-332 and 333-392 dimpled balls only for the purpose of simplification since a single set of formulas for all balls would be unduly complicated. However, no matter which set of formulas is used, best results are obtained when the golf ball has from about 315 to about 340 dimples and the following values are employed in the basic formula:

$$\begin{aligned}x &= 0.0117 \\y &= 0.156 \\a &= 1.1\end{aligned}$$

b = 0.55 This is designated as Formula 5. Golf balls which are within this best results formula will also be included within Formulas 2 and 4 and thus necessarily within Formulas 1 and 3.

The preferred method of applying the formulas is to plot a graph of d vs. D vs. N, holding S at 1. (For Formula 5, since there is no "N" in the formula the graph will simply be a plot of d vs. D holding S at 1.) The plotting of this graph is well within the skill of the art. Representative graphs are illustrated in FIGS. 19-25 as discussed hereinafter. Once the graph has been plotted, selection of one of the variables on the graph will automatically yield the other two variables.

An alternative method of applying the formulas is to first select the number of dimples to be used and then arbitrarily select a diameter and depth. If when these numbers are inserted in the appropriate formula $S = 1$ or less, then the depth and diameter are in accordance with the present invention. For Formula 5, the depths and diameters can be the same whether the number of dimples is about 315 or about 340 or any number therebetween.

The following will serve as illustrative examples of selecting diameter and depth according to the present invention. Of course, the dimples were positioned on the ball in accordance with the present invention.

EXAMPLE 1

In this case it was decided to have 252 dimples which comes within Formula 1. The diameter was selected as 0.175 inches and the depth as 0.0145 inches. These values were substituted into Formula 1 and S computed as about 1.9. Since S is greater than 1.0, the depth to diameter relationship is not in accordance with the present invention.

EXAMPLE 2

Example 1 was repeated holding the dimple number at 252 and the diameter at 0.175 inches. In this case, however, the depth of the dimple was decreased to 0.0135 inches. When these values were substituted into Formula 1, S equalled about 0.7 which is less than 1.0 and thus the depth to diameter relationship was in accordance with the present invention. These distances

4

are shown on FIG. 2 since they are within the present invention.

EXAMPLE 3

Example 2 was repeated using the same values i.e., 252 dimples, diameter of 0.175 inches and depth of 0.0135 inches. In this case, however, the values were substituted into Formula 3 to find out whether or not these values give "better" results. S was computed to be about 2.3 which is greater than 1.0 thereby indicating that these values, while within the present invention, do not give "better" results.

EXAMPLE 4

Example 3 was repeated holding the dimple number at 252 and the diameter at 0.175 inches but in this case the depth of the dimple was decreased to 0.0125 inches. When these values were substituted into Formula 3, S equalled about 0.4 which is less than 1.0 thereby indicating that these values give "better" results.

EXAMPLE 5

In this case it was decided to use 392 dimples, which comes within Formula 2. The diameter was selected as 0.130 inches and the depth as 0.009 inches. When these values were substituted into Formula 2, S was found to be about 3.0. Since S is greater than 1, the depth and diameter are not in the proper ratio in accordance with the present invention.

EXAMPLE 6

Example 5 was repeated holding the number of dimples at 392 and the depth at 0.009 inches. However, the diameter was increased to 0.140 inches. In this case S is 0.6 which is less than 1.0 and thus the depth to diameter relationship is within the limits of the present invention.

EXAMPLE 7

When Example 6 was repeated using the same values, i.e., 392 dimples, depth of 0.009 inches and diameter of 0.140 inches, but using Formula 4, S was computed to be 2.3. Since Formula 4 is the formula to be used to obtain "better" results and since the values of this example give a value greater than 1.0 in Formula 4, it is seen that these values, while within the present invention, do not give "better" results.

EXAMPLE 8

Example 7 was repeated holding the dimple number at 392 and the depth at 0.009 inches but in this case the diameter was increased to 0.145 inches. When these values were substituted into Formula 4, S was found to be 0.1. Since S is less than 1.0, these values give "better" results.

EXAMPLE 9

In this case it was decided to have 315 dimples which comes within the best results formula i.e., Formula 5. The diameter was selected as 0.150 inches and the depth as 0.0125 inches. These values were substituted into Formula 5 and S computed as about 0.8. Since S was less than 1.0, the depth to diameter relationship is within the "best results" of the present invention.

EXAMPLE 10

Example 9 was repeated using the same depth and diameter, i.e. 0.150 and 0.0125 inches, but in this case the golf ball had 340 dimples. Again, the S value

4,936,587

5

equalled 0.8 and thus the ball was within the "best results" region of the present invention.

These and other aspects of the present invention may be more fully understood with reference to the following drawings in which:

FIG. 1 is the top half of a golf ball with dimples arranged as in today's standard golf ball;

FIG. 2 is the top half of a golf ball showing dimples in accordance with the present invention;

FIGS. 3-5 are cross sections of dimples showing the method of determining the edge of the dimple; FIGS. 6-9 show a series of dimples and illustrate what is an "adjacent" dimple;

FIGS. 10-13 show one suitable method of arranging the dimples on the surface of the golf ball;

FIG. 14 shows the method of measuring the depth and diameter of a spherically shaped dimple;

FIGS. 15 and 16 show the method of computing the diameter of an irregularly shaped dimple;

FIGS. 17 and 18 show the method of computing the depth of an irregularly shaped dimple; and

FIGS. 19-25 show plots of diameter versus depth for 182, 252, 315, 332, 340, 392 and 362 dimples, respectively.

Referring now to FIG. 1, there is seen a golf ball partially in section with dimples arranged in the manner customarily employed today. Virtually, all golf balls on the market today have dimples arranged in accordance with this pattern. For each hemisphere of golf ball 10, the dimples 12 are arranged in two large rectangles 14 and 16, two small rectangles 18 and 20, and four triangles 22, 24, 26, and 28. Because of molding techniques, the opposite side of the golf ball virtually always has the same dimple pattern. It has been found that more than 33% of the land areas of adjacent dimples are more than 0.065 inches apart in this golf ball, even if the dimples are as large as 0.155 inches.

In FIG. 2 there is shown a golf ball made in accordance with the present invention. As indicated on the drawing, at least about 80% of the land areas of adjacent dimples are no greater than about 0.065 inches and no more than about 55% of the land areas of adjacent dimples are less than about 0.001 inches. As can be seen with reference to dimples 30 and 32, the distance 34 between the closest points of these two dimples may be more than 0.065 inches. It is only necessary that the distance between adjacent dimples be less than 0.065 inches for at least about 80% of such distances. Similarly, as can be seen with reference to dimples 36 and 38, there is a negative distance between the edges of the dimple since the edges overlap. In accordance with the present invention it is only necessary that at least about 55% of the distances between dimples at their closest points be greater than 0.001 inches. However, where the dimples overlap, the negative distance should in most cases be no greater than about 0.02 inches. The size of the dimples is relatively unimportant and can be varied within the diameters and depths as given hereinbefore. Different size dimples may be used on the same golf ball, if desired, provided that the critical distances between the edges of adjacent dimples at their closest points is maintained within the values as set forth herein.

Referring to FIGS. 3-5, there is seen the method of determining the point which comprises the edge of the dimple. The edge of the dimple is defined as that point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple,

6

said tangent being at a point about 0.003 inches from the periphery of the ball or its continuation.

In FIG. 3 is seen in cross section a golf ball having periphery 40 and continuation thereof 41 and dimple 12.

The periphery and its continuation are a substantially smooth section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects the dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery 40 at points C and D respectively. Points C and D are the edges of the dimple.

In FIG. 4 is seen a golf ball with dimple 12 which has a rounded top 44. The dimple, in three dimensions, is a section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery continuation 41 at points E and F respectively. Points E and F are the edges of the dimple.

Turning now to FIG. 5 there is shown a golf ball in cross section having dimples 12 and 12' partially shown with rounded tops 44 and 44'. Arc 42 is about 0.003 inches below curve 41-40-41 and intersects dimples 12 and 12' at points B and G respectively. Tangents 43' and 43'' are tangent to the dimples 12 and 12' at points B and G respectively. Tangents 43' and 43'' intersect periphery continuation 41 at points F and H respectively. Points F and H are the edges of dimples 12 and 12' respectively. The "land distance" between dimples 12 and 12' is measured along curve 41-40-41 from point F to point H.

Referring to FIGS. 6-9 there is seen the method of determining what is an "adjacent" dimple. An adjacent dimple is defined as one in which a triangle constructed of lines passing through the center points of 3 dimples has no included angle less than about 30°, and has no part of another dimple included therein.

Turning now to FIG. 6 there are shown 4 dimples, 45, 46, 48 and 50, having centers 52, 54, 56, and 58 respectively. If the center point of dimples 46, 48 and 50 are joined by lines, a triangle is formed having sides 60, 62, and 64 as shown. As can be seen, each of the included angles in this triangle is greater than about 30° and no part of another dimple is included within the triangle. Therefore, dimple 46 is adjacent to dimple 48, dimple 46 is adjacent to dimple 50, and dimple 48 is adjacent to dimple 50. Since in accordance with the present invention all dimples are circular or are converted to the circular, the closest points between the two dimples on the edges of the dimple will fall on the line which passes through the center of the two adjacent dimples. The closest points at the edges between dimples 46 and 48 are edge points 66 and 68, and therefore, the critical land distance as described hereinbefore is measured between points 66 and 68 for these adjacent dimples.

In FIG. 7 is shown of dimples 70, 72, 74, 76, 78, and 80, having centers 82, 84, 86, 88, 90, and 92, respectively. As shown with reference to FIG. 6, dimples 76 and 78 are "adjacent." If a triangle is formed by drawing lines through the center points of dimples 72, 78, and 76, it is seen that dimples 72 and 78 are not adjacent since the included angles formed by lines 94, 96, and by lines 94, 98 are less than 30°.

Referring to FIG. 8, there is again shown dimples 70, 72, 74, 76, 78, and 80, as well as dimples 100, 102 and 104. Lines 106, 108, and 110 form a triangle, passing through the centers of dimples 72, 78 and 104. Each of

4,936,587

7

the included angles of this triangle is greater than 30°. However, dimple 72 is not adjacent to dimple 78 since at least a part of another dimple is included within the triangle. In this case, the entire dimple 76 is included within the triangle and half of the dimple 80 is included within the triangle.

In FIG. 9 is shown a series of dimples 112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 136, 138, 140, 142, 144, 146, and 148. Referring to dimple 130, dimples 120, 122, 128, 132, 138, and 140 are adjacent thereto since a triangle can be formed with lines passing through the center points of each of these dimples without including at least a portion of another dimple and each included angle of the said triangles will be greater than about 30°. None of dimples 112, 114, 116, 118, 124, 126, 134, 136, 142, 144, 146, or 148 are adjacent to dimple 130 since no triangle can be drawn through the center point of three dimples including one of these dimples and dimple 130 which will not include at least a section of another dimple and which will have no angle of the triangle less than about 30°.

With further reference to FIG. 9, it will be understood that for dimple 122, adjacent dimples are 114, 116, 120, 124, 130 and 132. With reference to the dimple 140, the adjacent dimples are 130, 132, 138, 142, 146, and 148 and so forth with respect to each of the dimples. For determining the critical values of having at least about 80% of the dimples being no further apart than about 0.065 inches and at least about 55% of the dimples being no closer than about 0.001 inches, the distance between each dimple and each of its adjacent dimples is measured. However, duplicate measurements are not included. Thus, with respect to dimple 130, the distances between it and dimples 120, 122, 128, 132, 138, and 140, are included, but thereafter with respect to the dimple 122, the distance between it and dimple 130 would not be included since this has already been included with respect to dimple 130.

Maximum benefit is obtained when 100% of adjacent dimples have a distance between them at their closest points of less than about 0.065 inches and when 100% of the minimum distances between the closest points of adjacent dimples are greater than about 0.001 inches.

The mechanics of positioning the dimples on the golf ball is not our invention. One suitable method is to first determine the diameter of the dimple to be used. The diameter of the dimple is preferably within the range of about 0.125 inches to about 0.245 inches. The golf ball surface is then broken down into an icosahedron which, in effect, triangulates the surface of the golf ball as shown partially in FIG. 10. Each of the "triangles" of the icosahedron is equilateral as shown in FIG. 11. Vertex dimples 150, 152, and 154 are situated on each of the vertices of the triangle as shown with the center of the dimple being at the vertex of each angle. Additional dimples are then situated on the sides of the "triangle." The positioning of their centers is determined by the diameter of the dimple and the "land distance" between adjacent dimples which is held within the limits as previously given. The additional dimples on the sides of the "triangle" are shown in FIG. 12. Great circles are then made between dimples which are about equidistant from the vertex dimples connecting all of the center points of the dimples on the sides of the "triangle." Additional dimples are placed where these great circles intersect. As shown in FIG. 13, these great circles intersect at points 156, 158, and 160. These points are the center points for additional dimples. This procedure is

8

then followed with respect to each of the other "triangles" of the icosahedron. Naturally, a dimple at the vertex of three contiguous "triangles" will be a vertex dimple for each of the three triangles. It will be understood that the number of dimples on the sides of the "triangle" will vary inversely with the diameter of the dimple. According to the number of dimples on the sides of the "triangle," the number of great circles will also vary and therefore the number of dimples within the "triangle" will also vary since an additional dimple is placed wherever the great circles intersect.

The above method is only illustrative and need not be adhered to too rigidly and the dimples need not be evenly spaced so long as the spacing of the dimples is within the critical limitations as hereinbefore given. Golf balls are usually made with two mold "halves" and it is convenient to adjust the dimples in the vicinity of the mold line so that no dimples fall on the partition line of the molds. In this manner, there is less difficulty in removing any "flash" from a dimple.

In FIG. 14 is shown the method of measuring the depth and diameter of a spherically shaped dimple. The dimple in this case is shown in cross section and is the same dimple as shown in FIG. 4. The diameter is measured from the edges of the dimples, points E and F, along line 162 which is a straight line. Point J is the deepest part of the dimple 12. The depth is measured from point K on the continuation of the periphery 41 to point J and is indicated by line 164. Line 164 is perpendicular to line 162.

In FIGS. 15 and 16 is shown the method of computing the diameter of an irregularly shaped dimple. FIG. 15 shows the top of a hexagonally shaped dimple as one looks directly at it and all six sides 164 are shown at the edges of the dimple. The area of the hexagonally shaped dimple is approximately 0.01765 square inches. FIG. 16 is a circle which has an equivalent area to the hexagonal area of FIG. 15 i.e., the area of the circle of FIG. 16 is 0.01765 square inches. The diameter of FIG. 16 is shown as 166 and this diameter is approximately 0.150 inches. Thus, in accordance with the present invention, the diameter of the hexagonally shaped dimple of FIG. 15 is 0.150 inches. It is important to note that the diameter of an irregularly shaped dimple is not measured directly on the irregularly shaped dimple but is always a diameter of a circle which has an area equivalent to that of the irregularly shaped dimple.

In like manner, the depth of an irregularly shaped dimple is computed on the basis of a spherically shaped dimple. In FIG. 17 is shown a cross section of an irregularly shaped dimple which in this case is the same dimple as is shown in FIG. 15. For purposes of determining the depth of the dimple, the cross section is always taken across the widest part of the dimple which passes through the deepest part of the dimple. The edge of the dimple is shown at points L and M and was determined in accordance with the present invention as set out in FIGS. 3 and 4. The periphery is shown at 41 and the deepest point of the dimple is shown at point N. The area of the cross section of the dimple up to the continuation of the periphery (as shown, enclosed by lines M,N, N,L, and L,M along line 41) is computed and found to be 0.00113 square inches. The equivalent area of a section of a circle is then substituted for the dimple as shown in FIG. 18. Points O and P are the edges of the diameter of an equivalent dimple as determined in accordance with FIGS. 15 and 16 and line 168 is a straight line between lines O and P and corresponds to the diam-

4,936,587

9

eter line 166 of FIG. 16. Point R is the deepest part of the dimple and line 170 is perpendicular to line 168. Line 170 intersects the continuation of the periphery 41 at point S and the depth as measured from point S to point R is 0.0113 inches. It is important to note that in accordance with the present invention the depth of the dimple is measured from a cross section of a circle having an equivalent area to that of a cross section of the irregularly shaped dimple rather than being measured on the actual dimple.

As discussed hereinbefore, the preferred method of applying the various Formulas of the present invention is to plot a graph of dimple diameter against dimple depth at a given number of dimples and with S held at 1. Typical graphs are shown in FIGS. 19-25. FIG. 19 shows dimple and depth values for 182 dimples using Formula 1. FIG. 20 shows dimple and depth values for 252 dimples according to Formula 1. FIG. 21 shows dimple and depth values for 315 dimples according to Formula 1. FIG. 22 shows dimple and depth values for 332 dimples according to Formula 1. FIG. 23 shows dimple and depth values for 340 dimples according to Formula 2. FIG. 24 shows dimple and depth values for 392 dimples according to Formula 2. FIG. 25 shows dimple and depth values for 362 dimples according to Formula 2. As can be readily appreciated, the figures show a rotated ellipse. Thus, any value of S that is less than 1 is located within the ellipse and the center point of the ellipse is the point where S=0.

In all cases, measurements made in accordance with the present invention are made on a finished golf ball, since it is the final form of the golf ball which affects aerodynamic properties as opposed to some intermediate construction of the golf ball. In most cases, a finished golf ball will have one or more layers of paint affixed to the surface thereof and in these cases the measurements are made after the final coat of paint or other surface finish has been applied. With some of the new solid balls, however, a finished ball will not have any surface layer such as paint since it is not necessary. It will be understood that in these cases a finished ball means a ball that is unpainted. It will therefore be understood that the term "finished ball" can cover either a painted or an unpainted ball but in either case means the completed ball in the form in which it is intended to be sold to the consumer.

It will be understood that the claims are intended to cover all changes and modifications of the preferred embodiments of the invention, herein chosen for the purpose of illustration, which do not constitute departures from the spirit and scope of the invention.

We claim:

1. A finished golf ball which has from 182 to 392 dimples in the outer periphery thereof, the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches, and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation, and wherein combinations of the diameter D and depth d of all dimples formed on the ball are defined by the relationship:

10

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

10 in which:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

and wherein:

a value N is obtained by dividing the exact number of dimples by 100, and x, y, a and b are defined by the following relations as functions of N: when the number of dimples is between 182 and 332:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

and when the number of dimples is between 333 and 392:

$$y = 0.287 - 0.0383N$$

$$x = 0.0162 - 0.00150N$$

$$a = 4.66 - 0.500N$$

$$b = 5.00 - 1.08N.$$

2. The golf ball of claim 1 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

3. The golf ball of claim 1 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

4. The golf ball of claim 1 wherein the perimeter of each dimple is circular.

5. A finished golf ball having from 182 to 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

50 wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

4,936,587

11

6. The golf ball of claim 5 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

7. The golf ball of claim 5 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

8. The golf ball of claim 5 wherein the perimeter of each dimple is circular.

9. A finished golf ball having from 182 to 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.323-0.0896N+0.0122N²

x=0.0186-0.00406N+0.000550N²

a=4.54-2.78N+0.674N²

b=3.09-1.97N+0.412N²

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

10. The golf ball of claim 9 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

11. The golf ball of claim 9 wherein 100% of the distances between the closest points of the edges of the adjacent dimples is greater than 0.001 inches.

12. The golf ball of claim 9 wherein the perimeter of each dimple is circular.

13. A finished golf ball having from 315 to 340 dimples, the depth and diameter of the dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.156

x=0.0117

a=1.1

b=0.55

and the placement of the dimples being such that at least 80% of the distances between the closest points of the

12

edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

14. The golf ball of claim 13 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

15. The golf ball of claim 13 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

16. The golf ball of claim 13 wherein the perimeter of each dimple is circular.

17. A finished golf ball having on the surface thereof from 315 to 340 dimples, each said dimple being a section of a sphere, each said dimple having a diameter of 0.150 inches and a depth of 0.0125 inches, the dimples being arranged on the surface of the golf ball in the pattern of an icosahedron and the placement of the dimples being such that 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches and less than 0.065 inches.

18. A finished golf ball having from 333 to 392 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.287-0.0383N

x=0.0162-0.00150N

a=4.66-0.500N

b=5.00-1.08N

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

19. The golf ball of claim 18 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

20. The golf ball of claim 18 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

21. The golf ball of claim 18 wherein the perimeter of each dimple is circular.

4,936,587

13

22. A finished golf ball having from 333 to 392 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.240-0.0242N

x=0.0225-0.00340N

a=13.6-3.28N

b=5.25-1.25N

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

23. The golf ball of claim 22 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

24. The golf ball of claim 22 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

25. The golf ball of claim 22 wherein the perimeter of each dimple is circular.

26. A finished golf ball which has from 182 to 392 dimples in the outer periphery thereof, the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches, and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation, and wherein combinations of the diameter D and depth d of all dimples formed on the ball are defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

in which:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches and wherein:

14

a value N is obtained by dividing the exact number of dimples by 100, and x, y, a and b are defined by the following relations as functions of N:

when the number of dimples is between 182 and 332:

y=0.323-0.0896N+0.0122N²

x=0.0186-0.00406N+0.000550N²

a=6.30-3.30N+0.693N²

b=3.11-1.03N+0.155N²

and when the number of dimples is between 333 and 392:

y=0.287-0.0383N

x=0.0162-0.00150N

a=4.66-0.500N

b=5.00-1.08N and wherein the average diameter of all dimples in inches is greater than 0.150 inches.

27. The golf ball of claim 26 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

28. The golf ball of claim 26 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

29. The golf ball of claim 26 wherein the perimeter of each dimple is circular.

30. A finished golf ball having from 182 to 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.323-0.0896N+0.0122N²

x=0.0186-0.00406N+0.000550N²

a=6.30-3.30N+0.693N²

b=3.11-1.03N+0.155N²

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least 80% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation; and wherein the average diameter of all dimples in inches is greater than 0.150 inches.

31. The golf ball of claim 30 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

32. The golf ball of claim 30 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

33. The golf ball of claim 30 wherein the perimeter of each dimple is circular.

34. A finished golf ball having from 182 to 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

15

4,936,587

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

 $y=0.323-0.0896N+0.0122N^2$ $x=0.0186-0.00406N+0.000550N^2$ $a=4.54-2.78N+0.674N^2$ $b=3.09-1.97N+0.412N^2$

N=the exact number of dimples divided by 100

the placement of the dimples being such that at least 80% of the distances between the closest points of the

16

edges of adjacent dimples is less than 0.065 inches and at least 55% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation; and wherein the average diameter of all dimples in inches is greater than 0.150 inches.

35. The golf ball of claim 34 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than 0.065 inches.

36. The golf ball of claim 34 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

37. The golf ball of claim 34 wherein the perimeter of each dimple is circular.

* * * * *

25

30

35

40

45

50

55

60

65

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,936,587

DATED : June 26, 1990

Page 1 of 2

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the patent face, left-hand column, under the heading "FOREIGN PATENT DOCUMENTS", in the sixth patent listed change "12/1961" to --12/1916--;

On the patent face, right-hand column, fifth line, change "Gold" to --Golf--;

Column 1, line 39, change "dimples" to --dimple--;

Column 3, line 25, after "b=0.55" end the indentation and continue at the margin;

Column 5, line 11, after "dimple;" start a new paragraph;

Column 7, line 17, change "30" to --130--;

Column 8, line 39, change "sqaure" to --square--;

Column 10, line 17, after "of N:" start a new subparagraph;

Column 10, line 58, after "by 100" start a new subparagraph;

Column 11, line 28, after "by 100" start a new subparagraph;

Column 11, line 34, after "inches" insert --,--;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 4,936,587

DATED : June 26, 1990

Page 2 of 2

INVENTOR(S) : Francis deS. Lynch et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12, line 48, after "by 100" start a new subparagraph; and

Column 14, line 15, after "b=5.00-1.08N" start a new subparagraph.

Signed and Sealed this
Eleventh Day of September, 1990

Attest:

HARRY F. MANBECK, JR.

Attesting Officer

Commissioner of Patents and Trademarks

EXHIBIT C



US005080367A

United States Patent [19]

Lynch et al.

[11] Patent Number: **5,080,367**[45] Date of Patent: **Jan. 14, 1992**[54] **GOLF BALL**[75] Inventors: **Francis deS. Lynch, Mattapoisett; John W. Jepson, Marion; Robert A. Brown, Mattapoisett, all of Mass.**[73] Assignee: **Acushnet Company, New Bedford, Mass.**

[*] Notice: The portion of the term of this patent subsequent to Jun. 26, 2007.

[21] Appl. No.: **543,968**[22] Filed: **Jun. 26, 1990****Related U.S. Application Data**

[63] Continuation of Ser. No. 213,056, Dec. 4, 1980, Pat. No. 4,936,587, which is a continuation of Ser. No. 91,087, Nov. 5, 1979, abandoned, which is a continuation of Ser. No. 920,396, Jun. 29, 1978, abandoned, which is a continuation of Ser. No. 816,882, Jul. 18, 1977, abandoned, which is a continuation of Ser. No. 716,100, Aug. 20, 1976, abandoned, which is a continuation of Ser. No. 363,353, May 24, 1973, abandoned, which is a continuation-in-part of Ser. No. 236,318, Mar. 20, 1972, abandoned.

[51] Int. Cl.³ **A63B 37/14**[52] U.S. Cl. **273/232; 273/218**[58] Field of Search **273/232**[56] **References Cited****U.S. PATENT DOCUMENTS**

D. 27,441 7/1897 Dunn D21/205
 D. 29,949 1/1899 Barnes D21/205
 D. 30,378 3/1899 Foulis D21/205
 D. 34,557 5/1901 Cooper D21/205
 D. 41,327 4/1911 Pearce D21/205

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

201159 3/1955 Australia 273/232
 1005479 2/1977 Canada 273/232
 12884 of 1914 United Kingdom 273/232
 1-06134 12/1916 United Kingdom 273/232
 377354 7/1932 United Kingdom 273/232
 757183 9/1956 United Kingdom 273/232

OTHER PUBLICATIONS

"The Curious History of the Golf Ball, Mankind's Most Fascinating Sphere", Horizon Press, New York, 1968, pp. 127-130.

USGA, "The Rules of Golf", 1970, pp. 12-13.

"Golf-Exercise of One's Brains", p. 208 (Japan).

"A Guide to Golf Ball Engineering", pp. 772-773 (Japan).

"An Evening Newspaper of the Mainichi" (Japan).

"Iwanamis Dictionary of Mathematics", Feb. 20, 1971, pp. 581-582.

"Manual of Mechanical Engineering", Sep. 15, 1970, pp. 2-18.

"Encyclopedia of Science", Oct. 20, 1971, p. 168.

Primary Examiner—George J. Marlo

Attorney, Agent, or Firm—Lucas & Just

[57] **ABSTRACT**

A finished, painted golf ball is disclosed. Dimples on the golf ball are interrelated by dimple number, dimple diameter and dimple depth and are arranged on the surface of the golf ball in a manner which enables the golf ball to travel further. At least about 80% of the distances between the closest points of the edges of adjacent dimples are less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples are greater than about 0.001 inches.

Dimple number, dimple diameter and dimple depth are also interrelated in a specific manner according to the formula:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein:

d=average depth of all dimples in inches


D=average diameter of all dimples in inches

S=computed unknown (1.0 or less for present invention)

x, y, a and b are dependent on the number of dimples.

25 Claims, 13 Drawing Sheets

315 DIMPLES (FORMULA 1)



5,080,367

Page 2

U.S. PATENT DOCUMENTS

D. 41,698	8/1911	Royce	D21/205	D. 79,458	9/1929	Des Rosiers	D21/205
D. 41,817	10/1911	Pearce	D21/205	D. 80,740	3/1930	Perry	D21/205
D. 42,164	2/1912	Breakspear	D21/205	D. 91,919	4/1934	Burbank	D21/205
D. 43,673	3/1913	Johnston	D21/205	D. 94,403	1/1935	Burbank	D21/205
D. 44,109	5/1913	Penney	D21/205	D. 100,206	6/1936	Davis	D21/205
D. 44,175	6/1913	Martin et al.	D21/205	D. 102,940	1/1937	Cavignac	D21/205
D. 44,176	6/1913	Martin et al.	D21/205	D. 107,066	11/1937	Cavignac	D21/205
D. 44,177	6/1913	Martin et al.	D21/205	D. 108,065	1/1938	Cavignac	D21/205
D. 44,227	6/1913	Wood	D21/205	D. 176,470	12/1955	Martin	D21/205
D. 44,408	7/1913	Martin et al.	D21/205	D. 228,394	9/1973	Martin	273/232
D. 46,778	12/1914	Pearce	D21/205	697,417	4/1902	Kempshall	273/218
D. 46,783	12/1914	Worthington	D21/205	705,766	7/1902	Kempshall	273/220
D. 47,159	3/1915	Kempshall	D21/205	710,753	10/1902	Cavanagh	273/230
D. 49,905	11/1916	Martin	D21/204	716,945	12/1902	Seizer	273/230
D. 50,512	3/1917	Johnston	D21/205	878,254	2/1908	Taylor	273/232
D. 50,553	4/1917	Cochrane	D21/204	922,773	5/1909	Kempshall	273/232
D. 50,883	6/1917	Cochrane	D21/204	1,182,604	5/1916	Wadsworth	273/232
D. 51,722	2/1918	Eddy	D21/204	1,182,605	5/1916	Wadsworth	273/214
D. 52,500	9/1918	Vaile	D21/205	1,265,036	5/1918	Bendelow	273/232
D. 52,706	11/1918	Robertson	D21/205	1,286,834	12/1918	Taylor	273/232
D. 52,712	11/1918	Turner	D21/205	1,418,220	5/1922	White	273/232
D. 55,330	5/1920	Robertson	D21/204	1,517,514	12/1924	Hunt	273/232
D. 59,366	10/1921	Martin	D21/204	1,656,408	1/1928	Young	273/232
D. 60,979	5/1922	Cigol	D21/204	1,666,699	12/1928	Hagen	273/232
D. 72,692	7/1927	Beldam	D21/204	1,681,167	8/1928	Beldam	273/232
D. 72,693	7/1927	Beldam	D21/204	1,716,435	6/1929	Fotheringham	273/232
D. 73,046	7/1927	Penfold	D21/204	1,855,448	4/1932	Hazeltine	273/232
D. 74,213	1/1928	Cigol	D21/204	1,862,708	6/1932	Rosenberg	273/213
D. 75,198	5/1928	Young	D21/205	2,002,726	5/1935	Young	273/232
D. 75,422	6/1928	Gioggia	D21/205	2,106,704	2/1938	Davis	273/232
D. 78,311	4/1929	Perry	D21/205	2,135,210	11/1938	Farrar	273/232
D. 79,223	8/1929	Binnie	D21/205	2,728,576	12/1955	Martin et al.	273/232
D. 79,224	8/1929	Binnie	D21/205	4,090,716	5/1978	Martin et al.	273/232
				4,936,587	6/1990	Des Lynch	273/232

U.S. Patent

Jan. 14, 1992

Sheet 1 of 13

5,080,367

FIG. 1





FIG. 2






U.S. Patent

Jan. 14, 1992

Sheet 2 of 13

5,080,367






U.S. Patent

Jan. 14, 1992

Sheet 3 of 13

5,080,367



U.S. Patent

Jan. 14, 1992

Sheet 4 of 13

5,080,367




FIG. 9







FIG. 10

U.S. Patent

Jan. 14, 1992

Sheet 5 of 13

5,080,367



U.S. Patent

Jan. 14, 1992

Sheet 6 of 13

5,080,367




FIG. 14




FIG. 15




FIG. 16



FIG. 17




FIG. 18

U.S. Patent


Jan. 14, 1992

Sheet 7 of 13

5,080,367

FIG. 19.

182 DIMPLES (FORMULA 1)



U.S. Patent


Jan. 14, 1992

Sheet 8 of 13

5,080,367

FIG. 20.

25Z DIMPLES (FORMULA 1)




U.S. Patent

Jan. 14, 1992

Sheet 9 of 13

5,080,367

FIG. 21.



U.S. Patent


Jan. 14, 1992

Sheet 10 of 13

5,080,367

FIG. 22.

33Z DIMPLES (FORMULA 1)



U.S. Patent


Jan. 14, 1992

Sheet 11 of 13

5,080,367

FIG. 23.

340 DIMPLES (FORMULA 2)



U.S. Patent


Jan. 14, 1992

Sheet 12 of 13

5,080,367

FIG. 24.

392 DIMPLES (FORMULA 2)



U.S. Patent


Jan. 14, 1992

Sheet 13 of 13

5,080,367

FIG. 25.

362 DIMPLES (FORMULA 2)



5,080,367

1

GOLF BALL

This application is a continuation of application Ser. No. 213,056 filed Dec. 4, 1980, now U.S. Pat. No. 4,936,587 issued June 26, 1990, which in turn was a continuation of application Ser. No. 091,087 filed Nov. 5, 1979, now abandoned, which in turn was a continuation of application Ser. No. 920,396 filed June 29, 1978, now abandoned, which in turn was a continuation of application Ser. No. 816,882 filed July 18, 1977, now abandoned, which in turn was a continuation of application Ser. No. 716,100 filed Aug. 20, 1976, now abandoned, which in turn was a continuation of application Ser. No. 363,353 filed May 24, 1973, now abandoned, which in turn was a continuation-in-part of application Ser. No. 236,318 filed Mar. 20, 1972, now abandoned.

The present invention relates to the spatial relationships of dimples on the surface of golf balls. By having most of the adjacent dimples no more than about 0.065 inches apart, the golf ball will travel further than a standard golf ball which is identical except for the spatial arrangement of the dimples.

For many years golf balls have had dimples on their surfaces in order to increase their aerodynamic properties whereby the ball will travel further than a smooth golf ball. By the term "dimple" it is meant an indentation in the surface of a golf ball. There have been various attempts to improve the distance obtained from a golf ball by varying the configuration of an individual dimple such as by making its diameter larger, its depth shallower, or even changing the dimple from a round to a square configuration. It has now been discovered that increased yardage can be obtained from a golf ball in which the spatial relationships of the dimples are controlled so that at least about 80% of the land distances of adjacent dimples are less than about 0.065 inches and at least about 55% of the land distances of adjacent dimples are greater than about 0.001 inches. By the term "land distance" it is intended to mean the distance between the edges of two dimples at their closest points. The edge of the dimple is defined as the point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple and will be hereinafter more fully explained. Since only about 55% of the land distances are greater than about 0.001 inches, it will be understood that some of the dimples may overlap. Overlapping dimples may have a negative land distance as land distance is herein defined.

It has further been discovered that when the land area between adjacent dimples is controlled within the limits as set forth in this specification, the relative size and number of the dimples is unimportant. Standard golf balls contain about 336 ± 10 dimples on their surface. It has been found that the number of dimples on the golf ball can be varied substantially and that increased yardage will still be obtained when the limits on land distances as taught in this specification and claims are followed. It has additionally been found that the shape of the dimple is not critical. Although the preferred dimple is round, the dimple may be oval, pentagonal, hexagonal, octagonal or other shapes. In addition, more than one shape of dimple may be used on a single ball, if desired. When the term diameter is used herein, it is defined as the distance from edge to edge when the dimple is circular. When the dimple is non-circular, the term diameter is defined as the diameter of a circle which would have the same area as the area of the

2

non-circular dimple. When the term depth is used herein it is defined as the distance from the continuation of the periphery line to the deepest part of a dimple which is a section of a sphere. When the dimple is not a section of a sphere, the depth in accordance with the present invention is computed by taking a cross section of the dimple at its widest point. The area of the cross section is computed and then a section of a circle of equal area is substituted for the cross section. The depth is the distance from the continuation of the periphery line to the deepest part of the section of the circle. Golf balls according to the present invention have been made with 122 dimples, 182 dimples, 252 dimples, 332 dimples and 392 dimples among others.

The critical values in accordance with the present invention are that at least about 80% of the distances between the closest points of the edges of adjacent dimples must be less than about 0.065 inches and at least about 55% of the distances between the closest points of the edges of adjacent dimples must be greater than about 0.001 inches.

There is additional advantage in controlling the depth to diameter ratio of the individual dimples. In determining the depth to diameter ratio it is necessary to include the number of dimples to be used on the ball. The basic formula for this determination is as follows:

$$S = \left[\frac{831.5(d - x) - 55.56(D - y)}{a} \right]^2 + \left[\frac{83.15(D - y) + 555.6(d - x)}{b} \right]^2$$

wherein:

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

S=computed unknown (1.0 or less for present invention)

In accordance with the present invention, the computed unknown, S, will always be 1.0 or less. S can be equal to 0 but it will otherwise always be a positive number.

For a golf ball having from about 182 to about 332 dimples, the values of x, y, a, and b in accordance with the present invention will be:

$$y = 0.323 - 0.0896 N + 0.0122 N^2$$

$$x = 0.0186 - 0.00406 N + 0.000550 N^2$$

$$a = 6.30 - 3.30 N + 0.693 N^2$$

$$b = 3.11 - 1.03 N + 0.155 N^2$$

N=the exact number of dimples divided by 100

This is designated as Formula 1.

For a golf ball having from 333 to about 392 dimples the same basic formula is used with the following x, y, a, and b values:

$$y = 0.287 - 0.0383 N$$

$$x = 0.0162 - 0.00150 N$$

$$a = 4.66 - 0.500 N$$

$$b = 5.00 - 1.08 N$$

N=the exact number of dimples divided by 100

This is designated as Formula 2. Again, when S is equal to or less than 1 the depth to diameter relationship is in accordance with the present invention.

For golf balls having from 182 to 332 dimples, even better results are obtained with the basic formula when:

$$y = 0.323 - 0.0896 N + 0.0122 N^2$$

$$x = 0.0186 - 0.00406 N + 0.000550 N^2$$

$$a = 4.54 - 2.78 N + 0.674 N^2$$

$$b = 3.09 - 1.97 N + 0.412 N^2$$

N=the exact number of dimples divided by 100

5,080,367

3

This is designated as Formula 3. It is to be pointed out that all golf balls included in Formula 3 are also included in Formula 1.

For golf balls having from 333 to 392 dimples, even better results are obtained with the basic formula when:

$$\begin{aligned} y &= 0.240 - 0.0242 N \\ x &= 0.0225 - 0.00340 N \\ a &= 13.6 - 3.28 N \\ b &= 5.25 - 1.25 N \end{aligned}$$

N = the exact number of dimples divided by 100
This is designated as Formula 4. It is to be pointed out that all golf balls included in Formula 4 are also included in Formula 2.

It will be understood that there is not a sharp break between 332 and 333 dimples and that, in fact, the formulas given hereinbefore overlap in this general area. Different sets of formulas have been given for 182-332 and 333-392 dimpled balls only for the purpose of simplification since a single set of formulas for all balls would be unduly complicated. However, no matter which set of formulas is used, best results are obtained when the golf ball has from about 315 to about 340 dimples and the following values are employed in the basic formula:

$$\begin{aligned} x &= 0.0117 \\ y &= 0.156 \\ a &= 1.1 \\ b &= 0.55 \end{aligned}$$

This is designated as Formula 5. Golf balls which are within this best results formula will also be included within Formulas 2 and 4 and thus necessarily within Formulas 1 and 3.

The preferred method of applying the formulas is to plot a graph of d vs. D vs. N , holding S at 1. (For Formula 5, since there is no " N " in the formula the graph will simply be a plot of d vs. D holding S at 1). The plotting of this graph is well within the skill of the art. Representative graphs are illustrated in FIGS. 19-25 as discussed hereinafter. Once the graph has been plotted, selection of one of the variables on the graph will automatically yield the other two variables.

An alternative method of applying the formulas is to first select the number of dimples to be used and then arbitrarily select a diameter and depth. If when these numbers are inserted in the appropriate formula $S = 1$ or less, then the depth and diameter are in accordance with the present invention. For Formula 5, the depths and diameters can be the same whether the number of dimples is about 315 or about 340 or any number therebetween.

The following will serve as illustrative examples of selecting diameter and depth according to the present invention. Of course, the dimples were positioned on the ball in accordance with the present invention.

EXAMPLE 1

In this case it was decided to have 252 dimples which comes within Formula 1. The diameter was selected as 0.175 inches and the depth as 0.0145 inches. These values were substituted into Formula 1 and S computed as about 1.9. Since S is greater than 1.0, the depth to diameter relationship is not in accordance with the present invention.

EXAMPLE 2

Example 1 was repeated holding the dimple number at 252 and the diameter at 0.175 inches. In this case, however, the depth of the dimple was decreased to

4

0.0135 inches. When these values were substituted into Formula 1, S equalled about 0.7 which is less than 1.0 and thus the depth to diameter relationship was in accordance with the present invention. These distances are shown on FIG. 2 since they are within the present invention.

EXAMPLE 3

Example 2 was repeated using the same values i.e., 252 dimples, diameter of 0.175 inches and depth of 0.0135 inches. In this case, however, the values were substituted into Formula 3 to find out whether or not these values give "better" results. S was computed to be about 2.3 which is greater than 1.0 thereby indicating that these values, while within the present invention, do not give "better" results.

EXAMPLE 4

Example 3 was repeated holding the dimple number at 252 and the diameter at 0.175 inches but in this case the depth of the dimple was decreased to 0.0125 inches. When these values were substituted into Formula 3, S equalled about 0.4 which is less than 1.0 thereby indicating that these values give "better" results.

EXAMPLE 5

In this case it was decided to use 392 dimples, which comes within Formula 2. The diameter was selected as 0.130 inches and the depth as 0.009 inches. When these values were substituted into Formula 2, S was found to be about 3.0. Since S is greater than 1, the depth and diameter are not in the proper ratio in accordance with the present invention.

EXAMPLE 6

Example 5 was repeated holding the number of dimples at 392 and the depth at 0.009 inches. However, the diameter was increased to 0.140 inches. In this case S is 0.6 which is less than 1.0 and thus the depth to diameter relationship is within the limits of the present invention.

EXAMPLE 7

When Example 6 was repeated using the same values, i.e., 392 dimples, depth of 0.009 inches and diameter of 0.140 inches, but using Formula 4, S was computed to be 2.3. Since Formula 4 is the formula to be used to obtain "better" results and since the values of this example give a value greater than 1.0 in Formula 4, it is seen that these values, while within the present invention, do not give "better" results.

EXAMPLE 8

Example 7 was repeated holding the dimple number at 392 and the depth at 0.009 inches but in this case the diameter was increased to 0.145 inches. When these values were substituted into Formula 4, S was found to be 0.1. Since S is less than 1.0, these values give "better" results.

EXAMPLE 9

In this case it was decided to have 315 dimples which comes within the best results formula i.e., Formula 5. The diameter was selected as 0.150 inches and the depth as 0.0125 inches. These values were substituted into Formula 5 and S computed as about 0.8. Since S was less than 1.0, the depth to diameter relationship is within the "best results" of the present invention.

5,080,367

5

EXAMPLE 10

Example 9 was repeated using the same depth and diameter i.e., 0.150 inches and 0.0125 inches but in this case the golf ball had 340 dimples. Again, the S value equalled 0.8 and thus the ball was within the "best results" region of the present invention.

These and other aspects of the present invention may be more fully understood with reference to the following drawings in which:

FIG. 1 is the top half of a golf ball with dimples arranged as in today's standard golf ball;

FIG. 2 is the top half of a golf ball showing dimples in accordance with the present invention;

FIGS. 3-5 are cross sections of dimples showing the method of determining the edge of the dimple;

FIGS. 6-9 show a series of dimples and illustrate what is an "adjacent" dimple;

FIGS. 10-13 show one suitable method of arranging the dimples on the surface of the golf ball;

FIG. 14 shows the method of measuring the depth and diameter of a spherically shaped dimple;

FIGS. 15 and 16 show the method of computing the diameter of an irregularly shaped dimple;

FIGS. 17 and 18 show the method of computing the depth of an irregularly shaped dimple; and

FIGS. 19-25 show plots of diameter versus depth for 182, 252, 315, 332, 340, 392 and 362 dimples, respectively.

Referring now to FIG. 1, there is seen a golf ball partially in section with dimples arranged in the manner customarily employed today. Virtually, all golf balls on the market today have dimples arranged in accordance with this pattern. For each hemisphere of the golf ball 10, the dimples 12 are arranged in two large rectangles 14 and 16, two small rectangles 18 and 20, and four triangles 22, 24, 26, and 28. Because of molding techniques, the opposite side of the golf ball virtually always has the same dimple pattern. It has been found that more than 33% of the land areas of adjacent dimples are more than 0.065 inches apart in this golf ball, even if the dimples are as large as 0.155 inches.

In FIG. 2 there is shown a golf ball made in accordance with the present invention. As indicated on the drawing, at least about 80% of the land areas of adjacent dimples are no greater than about 0.065 inches and no more than about 55% of the land areas of adjacent dimples are less than about 0.001 inches. As can be seen with reference to dimples 30 and 32, the distance 34 between the closest points of these two dimples may be more than 0.065 inches. It is only necessary that the distance between adjacent dimples be less than 0.065 inches for at least about 80% of such distances. Similarly, as can be seen with reference to dimples 36 and 38, there is a negative distance between the edges of the dimple since the edges overlap. In accordance with the present invention it is only necessary that at least about 55% of the distances between dimples at their closest points be greater than 0.001 inches. However, where the dimples overlap, the negative distance should in most cases be no greater than about 0.02 inches. The size of the dimples is relatively unimportant and can be varied within the diameters and depths as given hereinbefore. Different size dimples may be used on the same golf ball, if desired, provided that the critical distances between the edges of adjacent dimples at their closest points is maintained within the values as set forth herein.

6

Referring to FIGS. 3-5, there is seen the method of determining the point which comprises the edge of the dimple. The edge of the dimple is defined as that point at which the periphery of the golf ball or its continuation intersects a tangent to the sidewall of the dimple, said tangent being at a point about 0.003 inches from the periphery of the ball or its continuation.

In FIG. 3 is seen in cross section a golf ball having periphery 40 and continuation thereof 41 and dimple 12. The periphery and its continuation are a substantially smooth section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects the dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery 40 at points C and D respectively. Points C and D are the edges of the dimple.

In FIG. 4 is seen a golf ball with dimple 12 which has a rounded top 44. The dimple, in three dimensions, is a section of a sphere. Arc 42 is about 0.003 inches below curve 40-41-40 and intersects dimple 12 at points A and B. Tangents 43 and 43' are tangent to the dimple 12 at points A and B respectively and intersect periphery continuation 41 at points E and F respectively. Points E and F are the edges of the dimple.

Turning now to FIG. 5 there is shown a golf ball in cross section having dimples 12 and 12' partially shown with rounded tops 44 and 44'. Arc 42 is about 0.003 inches below curve 41-40-41 and intersects dimples 12 and 12' at points B and G respectively. Tangents 43' and 43'' are tangent to the dimples 12 and 12' at points B and G respectively. Tangents 43' and 43'' intersect periphery continuation 41 at points F and H respectively. Points F and H are the edges of dimples 12 and 12' respectively. The "land distance" between dimples 12 and 12' is measured along curve 41-40-41 from point F to point H.

Referring to FIGS. 6-9 there is seen the method of determining what is an "adjacent" dimple. An adjacent dimple is defined as one in which a triangle constructed of lines passing through the center points of 3 dimples has no included angle less than about 30°, and has no part of another dimple included therein.

Turning now to FIG. 6 there are shown 4 dimples, 45, 46, 48 and 50, having centers 52, 54, 56, and 58 respectively. If the center point of dimples 46, 48 and 50 are joined by lines, a triangle is formed having sides 60, 62, and 64 as shown. As can be seen, each of the included angles in this triangle is greater than about 30° and no part of another dimple is included within the triangle. Therefore, dimple 46 is adjacent to dimple 48, dimple 46 is adjacent to dimple 50, and dimple 48 is adjacent to dimple 50. Since in accordance with the present invention all dimples are circular or are converted to the circular, the closest points between the two dimples on the edges of the dimple will fall on the line which passes through the center of the two adjacent dimples. The closest points at the edges between dimples 46 and 48 are edge points 66 and 68, and therefore, the critical land distance as described hereinbefore is measured between points 66 and 68 for these adjacent dimples.

In FIG. 7 is shown a set of dimples 70, 72, 74, 76, 78, and 80, having centers 82, 84, 86, 88, 90, and 92, respectively. As shown with reference to FIG. 6, dimples 76 and 78 are "adjacent." If a triangle is formed by drawing lines through the center points of dimples 72, 78, and 76, it is seen that dimples 72 and 78 are not adjacent

5,080,367

7

since the included angles formed by lines 94, 96, and by lines 94, 98 are less than 30°.

Referring to FIG. 8, there is again shown dimples 70, 72, 74, 76, 78, and 80, as well as dimples 100, 102 and 104. Lines 106, 108, and 110 form a triangle, passing through the centers of dimples 72, 78 and 104. Each of the included angles of this triangle is greater than 30°. However, dimple 72 is not adjacent to dimple 78 since at least a part of another dimple is included within the triangle. In this case, the entire dimple 76 is included within the triangle and half of the dimple 80 is included within the triangle.

In FIG. 9 is shown a series of dimples 112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 136, 138, 140, 142, 144, 146, and 148. Referring to dimple 130, dimples 120, 122, 128, 132, 138, and 140 are adjacent thereto since a triangle can be formed with lines passing through the center points of each of these dimples without including at least a portion of another dimple and each included angle of the said triangles will be greater than about 30°. None of dimples 112, 114, 116, 118, 124, 126, 134, 136, 142, 144, 146, or 148 are adjacent to dimple 130 since no triangle can be drawn through the center point of three dimples including one of these dimples and dimple 130 which will not include at least a section of another dimple and which will have no angle of the triangle less than about 30°.

With further reference to FIG. 9, it will be understood that for dimple 122, adjacent dimples are 114, 116, 120, 124, 130 and 132. With reference to the dimple 140, the adjacent dimples are 130, 132, 138, 142, 146, and 148 and so forth with respect to each of the dimples. For determining the critical values of having at least about 80% of the dimples being no further apart than about 0.065 inches and at least about 55% of the dimples being no closer than about 0.001 inches, the distance between each dimple and each of its adjacent dimples is measured. However, duplicate measurements are not included. Thus, with respect to dimple 130, the distances between it and dimples 120, 122, 128, 132, 138, and 140, are included, but thereafter with respect to the dimple 122, the distance between it and dimple 130 would not be included since this has already been included with respect to dimple 130.

Maximum benefit is obtained when 100% of adjacent dimples have a distance between them at their closest points of less than about 0.065 inches and when 100% of the minimum distances between the closest points of adjacent dimples are greater than about 0.001 inches.

The mechanics of positioning the dimples on the golf ball is not our invention. One suitable method is to first determine the diameter of the dimple to be used. The diameter of the dimple is preferably within the range of about 0.125 inches to about 0.245 inches. The golf ball surface is then broken down into an icosahedron which, in effect, triangulates the surface of the golf ball as shown partially in FIG. 10. Each of the "triangles" of the icosahedron is equilateral as shown in FIG. 11. Vertex dimples 150, 152, and 154 are situated on each of the vertices of the triangle as shown with the center of the dimple being at the vertex of each angle. Additional dimples are then situated on the sides of the "triangle." The positioning of their centers is determined by the diameter of the dimple and the "land distance" between adjacent dimples which is held within the limits as previously given. The additional dimples on the sides of the "triangle" are shown in FIG. 12. Great circles are then made between dimples which are about equidistant

8

from the vertex dimples connecting all of the center points of the dimples on the sides of the "triangle." Additional dimples are placed where these great circles intersect. As shown in FIG. 13, these great circles intersect at points 156, 158, and 160. These points are the center points for additional dimples. This procedure is then followed with respect to each of the other "triangles" of the icosahedron. Naturally, a dimple at the vertex of three contiguous "triangles" will be a vertex dimple for each of the three triangles. It will be understood that the number of dimples on the sides of the "triangle" will vary inversely with the diameter of the dimple. According to the number of dimples on the sides of the "triangle," the number of great circles will also vary and therefore the number of dimples within the "triangle" will also vary since an additional dimple is placed wherever the great circles intersect.

The above method is only illustrative and need not be adhered too rigidly and the dimples need not be evenly spaced so long as the spacing of the dimples is within the critical limitations as hereinbefore given. Golf balls are usually made with two mold "halves" and it is convenient to adjust the dimples in the vicinity of the mold line so that no dimples fall on the partition line of the molds. In this manner, there is less difficulty in removing any "flash" from a dimple.

In FIG. 14 is shown the method of measuring the depth and diameter of a spherically shaped dimple. The dimple in this case is shown in cross section and is the same dimple as shown in FIG. 4. The diameter is measured from the edges of the dimples, points E and F, along line 162 which is a straight line. Point J is the deepest part of the dimple 12. The depth is measured from point K on the continuation of the periphery 41 to point J and is indicated by line 164. Line 164 is perpendicular to line 162.

In FIGS. 15 and 16 is shown the method of computing the diameter of an irregularly shaped dimple. FIG. 15 shows the top of a hexagonally shaped dimple as one looks directly at it and all six sides 164 are shown at the edges of the dimple. The area of the hexagonally shaped dimple is approximately 0.01765 square inches. FIG. 16 is a circle which has an equivalent area to the hexagonal area of FIG. 15 i.e., the area of the circle of FIG. 16 is 0.01765 square inches. The diameter of FIG. 16 is shown as 166 and this diameter is approximately 0.150 inches. Thus, in accordance with the present invention, the diameter of the hexagonally shaped dimple of FIG. 15 is 0.150 inches. It is important to note that the diameter of an irregularly shaped dimple is not measured directly on the irregularly shaped dimple but is always a diameter of a circle which has an area equivalent to that of the irregularly shaped dimple.

In like manner, the depth of an irregularly shaped dimple is computed on the basis of a spherically shaped dimple. In FIG. 17 is shown a cross section of an irregularly shaped dimple which in this case is the same dimple as is shown in FIG. 15. For purposes of determining the depth of the dimple, the cross section is always taken across the widest part of the dimple which passes through the deepest part of the dimple. The edge of the dimple is shown at points L and M and was determined in accordance with the present invention as set out in FIGS. 3 and 4. The periphery is shown at 41 and the deepest point of the dimple is shown at point N. The area of the cross section of the dimple up to the continuation of the periphery (as shown, enclosed by lines M,N, N,L, and L,M along line 41) is computed and found to

5,080,367

9

be 0.00113 square inches. The equivalent area of a section of a circle is then substituted for the dimple as shown in FIG. 18. Points O and P are the edges of the diameter of an equivalent dimple as determined in accordance with FIGS. 15 and 16 and line 168 is a straight line between lines O and P and corresponds to the diameter line 166 of FIG. 16. Point R is the deepest part of the dimple and line 170 is perpendicular to line 168. Line 170 intersects the continuation of the periphery 41 at point S and the depth as measured from point S to point R is 0.0113 inches. It is important to note that in accordance with the present invention the depth of the dimple is measured from a cross section of a circle having an equivalent area to that of a cross section of the irregularly shaped dimple rather than being measured on the actual dimple.

As discussed hereinbefore, the preferred method of applying the various Formulas of the present invention is to plot a graph of dimple diameter against dimple depth at a given number of dimples and with S held at 1. Typical graphs are shown in FIGS. 19-25. FIG. 19 shows dimple and depth values for 182 dimples using Formula 1. FIG. 20 shows dimple and depth values for 252 dimples according to Formula 1. FIG. 21 shows dimple and depth values for 315 dimples according to Formula 1. FIG. 22 shows dimple and depth values for 332 dimples according to Formula 1. FIG. 23 shows dimple and depth values for 340 dimples according to Formula 2. FIG. 24 shows dimple and depth values for 392 dimples according to Formula 2. FIG. 25 shows dimple and depth values for 362 dimples according to Formula 2. As can be readily appreciated, the figures show a rotated ellipse. Thus, any value of S that is less than 1 is located within the ellipse and the center point of the ellipse is the point where S=0.

In all cases, measurements made in accordance with the present invention are made on a finished golf ball, since it is the final form of the golf ball which affects aerodynamic properties as opposed to some intermediate construction of the golf ball. In most cases, a finished golf ball will have one or more layers of paint affixed to the surface thereof and in these cases the measurements are made after the final coat of paint or other surface finish has been applied. With some of the new solid balls, however, a finished ball will not have any surface layer such as paint since it is not necessary. It will be understood that in these cases a finished ball means a ball that is unpainted. It will therefore be understood that the term "finished ball" can cover either a painted or an unpainted ball but in either case means the completed ball in the form in which it is intended to be sold to the consumer.

It will be understood that the claims are intended to cover all changes and modifications of the preferred embodiments of the invention, herein chosen for the purpose of illustration, which do not constitute departures from the spirit and scope of the invention.

What is claimed is:

1. A finished, painted golf ball which has from about 182 to about 392 dimples in the outer periphery thereof, the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches, and at least about 55% of the distances between the closest points of the edges of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to

10

the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation, and wherein combinations of the diameter D and depth d of all dimples formed on the ball are defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

in which

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

and wherein a value N is obtained by dividing the exact number of dimples by 100, and x, y, a and b are defined by the following relations as functions of N:

when the number of dimples is between 182 and 332:

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

when the number of dimples is between 333 and 392:

$$y = 0.287 - 0.0383N$$

$$x = 0.0162 - 0.00150N$$

$$a = 4.66 - 0.500N$$

$$b = 5.00 - 1.08N$$

2. The golf ball of claim 1 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

3. The golf ball of claim 1 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

4. The golf ball of claim 1 wherein the perimeter of each dimple is circular.

5. A finished, painted golf ball having from about 182 to 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

$$y = 0.323 - 0.0896N + 0.0122N^2$$

$$x = 0.0186 - 0.00406N + 0.000550N^2$$

$$a = 6.30 - 3.30N + 0.693N^2$$

$$b = 3.11 - 1.03N + 0.155N^2$$

N=the exact number of dimples divided by 100

and the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches and at least about 55% of the distances between the closest points of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

5,080,367

11

6. The golf ball of claim 5 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

7. The golf ball of claim 5 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

8. The golf ball of claim 5 wherein the perimeter of each dimple is circular.

9. A finished, painted golf ball having from about 182 to about 332 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.323-0.0896N+0.0122N²

x=0.0186-0.00406N+0.000550N²

a=4.54-2.78N+0.674N²

b=3.09-1.97N+0.412N²

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches and at least about 55% of the distances between the closest points of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

10. The golf ball of claim 9 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

11. The golf ball of claim 9 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

12. The golf ball of claim 9 wherein the perimeter of each dimple is circular.

13. A finished, painted golf ball having from about 315 to about 340 dimples, the depth and diameter of the dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.156

x=0.0117

a=1.1

b=0.55

and the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065

12

inches and at least about 55% of the distances between the closest points of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

14. The golf ball of claim 13 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

15. The golf ball of claim 13 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

16. The golf ball of claim 13 wherein the perimeter of each dimple is circular.

17. A finished, painted golf ball having on the surface thereof from about 315 to about 340 dimples, each said dimple being a section of a sphere, each said dimple having a diameter of about 0.150 inches and a depth of about 0.0125 inches, the dimples being arranged on the surface of the golf ball in the pattern of an icosahedron and the placement of the dimples being such that 100% of the distances between the closest points of the edges of adjacent dimples is greater than about 0.001 inches and less than about 0.065 inches.

18. A finished, painted golf ball having from about 333 to about 392 dimples, the depth, diameter and number of dimples being defined by the relationship:

$$S = \left[\frac{831.5(d-x) - 55.56(D-y)}{a} \right]^2 + \left[\frac{83.15(D-y) + 555.6(d-x)}{b} \right]^2$$

wherein

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.287-0.383N

x=0.0162-0.00150N

a=4.66-0.500N

b=5.00-1.08N

N=the exact number of dimples divided by 100 and the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches and at least about 55% of the distances between the closest points of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point about 0.003 inches below the periphery of the golf ball or its continuation.

19. The golf ball of claim 18 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

20. The golf ball of claim 18 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

21. The golf ball of claim 18 wherein the perimeter of each dimple is circular.

22. A finished, painted golf ball having from about 333 to about 392 dimples, the depth, diameter and number of dimples being defined by the relationship:

13

5,080,367

$$S = \left[\frac{831.5(d - x) - 55.56(D - y)}{a} \right]^2 + \left[\frac{83.15(D - y) + 555.6(d - x)}{b} \right]^2$$

wherein

S=a value of 0 to 1.0

d=average depth of all dimples in inches

D=average diameter of all dimples in inches

y=0.240-0.0242N

x=0.0225-0.00340N

a=13.6-3.28N

b=5.25-1.25N

N=the exact number of dimples divided by 100

14

and the placement of the dimples being such that at least about 80% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches and at least about 55% of the distances between the closest points of adjacent dimples is greater than about 0.001 inches, the edge of the dimple being defined as the point of intersection of the periphery of the golf ball or its continuation and a tangent to the sidewall of the dimple at a point 0.003 inches below the periphery of the golf ball or its continuation.

23. The golf ball of claim 22 wherein 100% of the distances between the closest points of the edges of adjacent dimples is less than about 0.065 inches.

24. The golf ball of claim 22 wherein 100% of the distances between the closest points of the edges of adjacent dimples is greater than 0.001 inches.

25. The golf ball of claim 22 wherein the perimeter of each dimple is circular.

* * * * *

20

25

30

35

40

45

50

55

60

65

EXHIBIT D

**IN THE UNITED STATES DISTRICT COURT
DISTRICT OF DELAWARE**

BRIDGESTONE SPORTS CO., LTD.,
AND BRIDGESTONE GOLF, INC.,

Plaintiff,

v.

ACUSHNET COMPANY,

Defendant.

)
)
)
)
) C.A. No. 05-132(JJF)
)
)
)
)
)

DEFENDANT'S FIRST SET OF INTERROGATORIES TO PLAINTIFF

Pursuant to Rule 33 of the Federal Rules of Civil Procedure, defendant Acushnet Company ("Acushnet") hereby requests that plaintiff Bridgestone Sports Co., Ltd. and Bridgestone Golf, Inc. (collectively "Bridgestone") answer the following interrogatories in the time required by law at the offices of Howrey LLP, 1299 Pennsylvania Avenue, NW, Washington DC 20004.

DEFINITIONS

The following definitions apply to these requests:

1. The term "Bridgestone" or "you" or "your" shall mean Bridgestone Sports Co., Ltd., Bridgestone Golf, Inc., and any parent, subsidiary, partner (including general and limited partners), member and/or affiliated entities, past or present, of Bridgestone, and any person or entity, past or present, acting on behalf of Bridgestone, including each of its present and former officers, executives, general partners, limited partners, directors, employees, attorneys, agents and/or representatives.

2. The term "Acushnet" as used herein each shall refer to the named defendant, Acushnet Company and its present and/or former officers, directors, employees, agents, attorneys, and/or representatives.

“Bridgestone has not infringed and does not infringe, either directly or indirectly and either literally or by application of the doctrine of equivalents,” any claim of any of the Acushnet Patents, including all witnesses with knowledge of such facts and all documents that support such facts.

INTERROGATORY NO. 17.

If Bridgestone alleges the invention in the United States of any apparatus, product, device, process, method, act or other instrumentality that practiced any invention claimed in the Acushnet Patents prior to the earliest claimed priority date of such claims, identify, separately for each such claim, the circumstances of such prior invention, including all places or facilities involved in research and development related to the prior invention, all persons involved in the conception and reduction to practice of the prior invention, and the dates of conception and reduction to practice of the prior invention.

INTERROGATORY NO. 18.

Identify on a claim-by-claim basis for each one of the Acushnet Patents that Bridgestone contends is invalid and provide a chart identifying specifically under which section(s) of the Patent Code that Bridgestone contends each identified claim is invalid and how Bridgestone contends that each identified claim fails to satisfy such section(s), including where, specifically, in the prior art Bridgestone contends a teaching or suggestion of or motivation to combine each element of each identified claim is found.

INTERROGATORY NO. 19.

Identify all publications and other materials alleged by Bridgestone to be relevant to the patentability of the Acushnet Patents, including each document, thing, or other evidence supporting the chart requested in Interrogatory No. 18.

EXHIBIT E

**THIS EXHIBIT HAS BEEN
REDACTED IN ITS ENTIRETY**